



Flood Risk Report

*Jefferson County Coastal Project Area, Texas**

Portions of 12020003 (Lower Neches), 12020007 (Pine Island Bayou), 12040201 (Sabine Lake), 12040202 (East Galveston Bay), Texas

* Spans more than one watershed. This report only covers the studied area within each watershed.

Report Number *01*

10/15/2014

Final



FEMA

RiskMAP
Increasing Resilience Together

Project Area Community List

Community Name
City of Beaumont*
City of Groves*
City of Nederland
City of Port Arthur*
City of Port Neches*
City of Taylor Landing
Jefferson County Unincorporated Areas*

*Spans more than one watershed. This report only covers the coastal project area.

Preface

The Department of Homeland Security (DHS), Federal Emergency Management Agency's (FEMA) Risk Mapping, Assessment, and Planning (Risk MAP) program provides states, tribes, and local communities with flood risk information and tools that they can use to increase their resilience to flooding and better protect their citizens. By pairing accurate floodplain maps with risk assessment tools and planning and outreach support, Risk MAP has transformed traditional flood mapping efforts into an integrated process of identifying, assessing, communicating, planning for, and mitigating flood-related risks.

This Flood Risk Report (FRR) provides non-regulatory information to help local or tribal officials, floodplain managers, planners, emergency managers, and others better understand their flood risk, take steps to mitigate those risks, and communicate those risks to their citizens and local businesses.

Because flood risk often extends beyond community limits, the FRR provides flood risk data for the entire Flood Risk Project as well as for each individual community. This also emphasizes that flood risk reduction activities may impact areas beyond jurisdictional boundaries.

Flood risk is always changing, and there may be other studies, reports, or sources of information available that provide more comprehensive information. The FRR is not intended to be regulatory or the final authoritative source of all flood risk data in the project area. Rather, it should be used in conjunction with other data sources to provide a comprehensive picture of flood risk within the project area.

Table of Contents

1	Introduction.....	1
1.1	About Flood Risk	1
1.1.1	Calculating Flood Risk	1
1.1.2	Risk MAP Flood Risk Products.....	1
1.2	Uses of this Report	2
1.3	Sources of Flood Risk Assessment Data Used.....	3
1.4	Related Resources	4
2	Flood Risk Analysis.....	5
2.1	Overview	5
2.2	Analysis of Risk	5
2.2.1	Changes Since Last FIRM	6
2.2.2	Flood Depth and Analysis Grids.....	7
2.2.3	Estimated Flood Loss Information.....	8
2.2.4	Areas of Mitigation Interest	10
3	Flood Risk Analysis Results	18
3.1	Flood Risk Map.....	19
3.2	Jefferson County Coastal Project Area Flood Risk Project Summary	21
3.2.1	Overview.....	21
3.2.2	Flood Risk Datasets	22
3.3	Communities	25
3.3.1	City of Beaumont (CID 485457)	25
3.3.2	City of Groves (CID 485475)	29
3.3.3	City of Nederland (CID 485492)	34
3.3.4	City of Port Arthur (CID 485499)	39
3.3.5	City of Port Neches (CID 485500)	43
3.3.6	City of Taylor Landing (CID 481698).....	48
3.3.7	Jefferson County Unincorporated Areas (CID 480385)	53
4	Actions to Reduce Flood Risk	57
4.1	Types of Mitigation Actions	57
4.1.1	Preventative Measures	57
4.1.2	Property Protection Measures	58
4.1.3	Natural Resource Protection Activities.....	58

4.1.4	Structural Mitigation Projects	58
4.1.5	Public Education and Awareness Activities	58
4.1.6	Emergency Service Measures	59
4.2	Identifying Specific Actions for Your Community.....	59
4.3	Mitigation Programs and Assistance.....	60
4.3.1	FEMA Mitigation Programs and Assistance	60
4.3.2	Additional Mitigation Programs and Assistance	61
5	Acronyms and Definitions	62
5.1	Acronyms	62
5.2	Definitions.....	63
6	Additional Resources	66
7	Data Used to Develop Flood Risk Products	68

FLOOD RISK REPORT

1 Introduction

1.1 About Flood Risk

Floods are naturally occurring phenomena that can and do happen almost anywhere. In its most basic form, a flood is an accumulation of water over normally dry areas. Floods become hazardous to people and property when they inundate an area where development has occurred, causing losses. Mild flood losses may have little impact on people or property, such as damage to landscaping or the generation of unwanted debris. Severe flooding can destroy buildings, ruin crops, and cause critical injuries or death.

1.1.1 Calculating Flood Risk

It is not enough to simply identify where flooding may occur. Just because one knows where a flood occurs does not mean they know the **risk** of flooding. The most common method for determining flood risk, also referred to as vulnerability, is to identify the probability of flooding and the consequences of flooding. In other words:

- Flood Risk (or Vulnerability) = Probability x Consequences; where
- Probability = the likelihood of occurrence
- Consequences = the estimated impacts associated with the occurrence

The probability of a flood is the likelihood that a flood will occur. The probability of flooding can change based on physical, environmental, and/or contributing engineering factors. Factors affecting the probability that a flood will impact an area range from changing weather patterns to the existence of mitigation projects. The ability to assess the probability of a flood and the level of accuracy for that assessment are also influenced by modeling methodology advancements, better knowledge, and longer periods of record for the water body in question.

The consequences of a flood are the estimated impacts associated with the flood occurrence. Consequences relate to humans activities within an area and how a flood impacts the natural and built environments.

1.1.2 Risk MAP Flood Risk Products

Through Risk MAP, FEMA provides communities with updated Flood Insurance Rate Maps (FIRMs) and Flood Insurance Studies (FISs) that focus on the probability of floods and that show where flooding may occur as well as the calculated 1% annual chance flood elevation. The



Flooding is a natural part of our world and our communities. Flooding becomes a significant hazard, however, when it intersects with the built environment.

Which picture below shows more flood risk?



Even if you assume that the flood in both pictures was the same probability—let's say a 10-percent-annual-chance flood—the consequences in terms of property damage and potential injury as a result of the flood in the bottom picture are much more severe. Therefore, the flood risk in the area shown in the bottom picture is higher.

1% annual chance flood, also known as the base flood, has a 1% chance of being equaled or exceeded in any given year. FEMA understands that flood risk is dynamic—that flooding does not stop at a line on a map—and as such, provides the following flood risk products:

- **Flood Risk Report (FRR):** The FRR presents key risk analysis data for the Flood Risk Project.
- **Flood Risk Map (FRM):** Like the example found in Section 3.1 of this document, the FRM shows a variety of flood risk information in the project area. More information about the data shown on the FRM may be found in Section 2 of this report.
- **Flood Risk Database (FRD):** The FRD is in GIS format and houses the flood risk data developed during the course of the flood risk analysis that can be used and updated by the community. After the Flood Risk Project is complete, this data can be used in many ways to visualize and communicate flood risk within the Flood Risk Project.



Whether or not an area might flood is one consideration. The extent to which it might flood adds a necessary dimension to that understanding.

These Flood Risk Products provide flood risk information at both the Flood Risk Project level and community level (for those portions of each community within the Flood Risk Project). They demonstrate how decisions made within a Flood Risk Project can impact properties downstream, upstream, or both. Community-level information is particularly useful for mitigation planning and emergency management activities, which often occur at a jurisdictional level.

1.2 Uses of this Report

The goal of this report is to help inform and enable communities and tribes to take action to reduce flood risk. Possible users of this report include:

- Local elected officials
- Floodplain managers
- Community planners
- Emergency managers
- Public works officials
- Other special interests (e.g., watershed conservation groups, environmental awareness organizations, etc.)



Vulnerability of infrastructure is another important consideration.

State, local, and tribal officials can use the summary information provided in this report, in conjunction with the data in the FRD, to:

- **Update local hazard mitigation plans.** As required by the 2000 Federal Stafford Act, local hazard mitigation plans must be updated at least every five (5) years. Summary information presented in Section 3 of this report and the FRM can be used to identify areas that may need additional focus when updating the risk assessment section of a local hazard mitigation plan. Information found in Section 4 pertains to the different mitigation techniques and programs and can be used to inform decisions related to the mitigation strategy of local plans.

- **Update community comprehensive plans.** Planners can use flood risk information in the development and/or update of comprehensive plans, future land use maps, and zoning regulations. For example, zoning codes may be changed to better provide for appropriate land uses in high-hazard areas.
- **Update emergency operations and response plans.** Emergency managers can identify low-risk areas for potential evacuation and sheltering and can help first responders avoid areas of high-depth flood water. Risk assessment results may reveal vulnerable areas, facilities, and infrastructure for which planning for continuity of operations plans (COOP), continuity of government (COG) plans, and emergency operations plans (EOP) would be essential.
- **Develop hazard mitigation projects.** Local officials (e.g., planners and public works officials) can use flood risk information to re-evaluate and prioritize mitigation actions in local hazard mitigation plans.
- **Communicate flood risk.** Local officials can use the information in this report to communicate with property owners, business owners, and other citizens about flood risks, changes since the last FIRM, and areas of mitigation interest. The report layout allows community information to be extracted in a fact sheet format.
- **Inform the modification of development standards.** Floodplain managers, planners, and public works officials can use information in this report to support the adjustment of development standards for certain locations. For example, heavily developed areas tend to increase floodwater runoff because paved surfaces cannot absorb water, indicating a need to adopt or revise standards that provide for appropriate stormwater retention.




Flooding along the Wabash River in Clark County, Illinois, contributed to a federal disaster declaration on June 24, 2008.

The Flood Risk Database, Flood Risk Map, and Flood Risk Report are “non-regulatory” products. They are available and intended for community use but are neither mandatory nor tied to the regulatory development and insurance requirements of the National Flood Insurance Program (NFIP). They may be used as regulatory products by communities if authorized by state and local enabling authorities.

1.3 Sources of Flood Risk Assessment Data Used

To assess potential community losses, or the consequences portion of the “risk” equation, the following data is typically collected for analysis and inclusion in a Flood Risk Project:

- Information about local assets or resources at risk of flooding
- Information about the physical features and human activities that contribute to that risk
- Information about where the risk is most severe




For most Flood Risk Projects, FEMA uses the following sources of flood risk information to develop this report:

- Hazus estimated flood loss information
- New engineering analyses (e.g., hydrology and hydraulic modeling) to develop new flood boundaries
- Locally supplied data (see Section 7 for a description)
- Sources identified during the Discovery process

1.4 Related Resources

For a more comprehensive picture of flood risk, FEMA recommends that state and local officials use the information provided in this report in conjunction with other sources of flood risk data, such as those listed below.

- **FIRMs and FISs.** This information indicates areas with specific flood hazards by identifying the limit and extent of the 1-percent-annual-chance floodplain and the 0.2-percent-annual-chance floodplain. FIRMs and FIS Reports do not identify all floodplains in a Flood Risk Project. The FIS Report includes summary information regarding other frequencies of flooding, as well as flood profiles for riverine sources of flooding. In rural areas and areas for which flood hazard data are not available, the 1-percent-annual-chance floodplain may not be identified. In addition, the 1-percent-annual-chance floodplain may not be identified for flooding sources with very small drainage areas (less than 1 square mile).
- **Hazus Flood Loss Estimation Reports.** Hazus can be used to generate reports, maps and tables on potential flood damage that can occur based on new/proposed mitigation projects or future development patterns and practices. Hazus can also run specialized risk assessments, such as what happens when a dam or levee fails. Flood risk assessment tools are available through other agencies as well, including the National Oceanic and Atmospheric Administration (NOAA) and the U.S. Army Corps of Engineers (USACE). Other existing watershed reports may have a different focus, such as water quality, but may also contain flood risk and risk assessment information. See Section 6 for additional resources.
- **Flood or multi-hazard mitigation plans.** Local hazard mitigation plans include risk assessments that contain flood risk information and mitigation strategies that identify community priorities and actions to reduce flood risk. This report was informed by any existing mitigation plans in the Flood Risk Project.
- **FEMA Map Service Center (MSC).** The MSC has useful information, including fly sheets, phone numbers, data, etc. Letters of Map Change are also available through the MSC. The user can view FIRM databases and the National Flood Hazard Layer (NFHL) Database.



FEMA data can be leveraged to identify and measure vulnerability by including local building information (i.e. building type). The examples above show various ways to display flooding intersecting with buildings.

2 Flood Risk Analysis

2.1 Overview

Flood hazard identification uses FIRMs, and FIS Reports identify where flooding can occur along with the probability and depth of that flooding. Flood risk assessment is the systematic approach to identifying how flooding impacts the environment. In hazard mitigation planning, flood risk assessments serve as the basis for mitigation strategies and actions by defining the hazard and enabling informed decision making. Fully assessing flood risk requires the following:

- Identifying the flooding source and determining the flood hazard occurrence probability
- Developing a complete profile of the flood hazard including historical occurrence and previous impacts
- Inventorying assets located in the identified flood hazard area
- Estimating potential future flood losses caused by exposure to the flood hazard area

Flood risk analyses are different methods used in flood risk assessment to help quantify and communicate flood risk. Flood risk analysis can be performed on a large scale (state, community) level and on a very small scale (parcel, census block). Advantages of large-scale flood risk analysis, especially at the watershed level, include identifying how actions and development in one community can affect areas up- and downstream. On the parcel or census block level, flood risk analysis can provide actionable data to individual property owners so they can take appropriate mitigation steps.



Flooding impacts non-populated areas too, such as agricultural lands and wildlife habitats.

2.2 Analysis of Risk

The FRR, FRM, and FRD contain a variety of flood risk analysis information to help describe and visualize flood risk within the project area. Depending on the scope of the Flood Risk Project for this project area, this information may include some or all of the following elements:

- Changes Since Last FIRM
- Water Surface, Flood Depth, and Analysis Grids
- Flood Risk Assessment Information
- Areas of Mitigation Interest

State and Local Hazard Mitigation Plans are required to have a comprehensive all-hazard risk assessment. The flood risk analyses in the FRR, FRM, and FRD can inform the flood hazard portion of a community's or state's risk assessment. Further, data in the FRD can be used to develop information that meets the requirements for risk assessments as it relates to the hazard of flood in hazard mitigation plans.

2.2.1 Changes Since Last FIRM



The Changes Since Last FIRM (CSLF) dataset, stored in the FRD and shown in Section 3 of this report, illustrates where changes to flood risk may have occurred since the last FIRM was published for the subject area. Communities can use this information to update their mitigation plans, specifically quantifying “what is at risk” and identifying possible mitigation activities.

The CSLF dataset identifies changes in the Special Flood Hazard Area (SFHA) and floodway boundary changes since the previous FIRM was developed. These datasets quantify land area increases and decreases to the SFHA and floodway, as well as areas where the flood zone designation has changed (e.g., Zone A to AE, AE to VE, shaded Zone X protected by levee to AE for de-accredited levees).

The CSLF dataset is created in areas that were previously mapped using digital FIRMs. The CSLF dataset for this project area includes:

- Floodplain and/or Floodway Boundary Changes: Any changes to the existing floodplain or floodway boundaries are depicted in this dataset
- Floodplain Designation Changes: This includes changed floodplain designations (e.g., Zone A to Zone AE).
- CSLF Information: Within this dataset additional information is provided to help explain the floodplain and floodway boundary changes shown on the FIRM. This information is stored as digital attributes within the CSLF polygons and may include some or all of the following:
 - o Changes in peak discharges
 - o Changes to the modeling methodology (e.g., tide gage analysis)
 - o New flood control structures (e.g., dams, levees, etc.)
 - o Changes to hydraulic structures (e.g., bridges, culverts, etc.)
 - o Sedimentation and/or Erosion
 - o Man-made changes to a watercourse (e.g., realignment or improvement)

It should be noted that reasons for the floodplain and floodway changes (also known as Contributing Engineering Factors) are intended to give the user a general sense of what caused the change, as opposed to providing a reason for each and every area of change.



Floodplain maps have evolved considerably from the older paper-based FIRMs to the latest digital products and datasets.

CSLF data can be used to communicate changes in the physical flood hazard area (size, location) as part of the release of new FIRMS. It can also be used in the development or update of hazard mitigation plans to describe changes in hazard as part of the hazard profile.


CSLF data is shown in the FRR, and underlying data is stored in the FRD.

2.2.2 Flood Depth and Analysis Grids

Grids are FEMA datasets provided in the FRD to better describe the risk of the flood hazard. While the FIRM and FIS Report describe “what” is at risk by identifying the hazard areas, water surface, flood depth, and analysis grids can help define “how bad” the risk is within those identified areas. These grids are intended to be used by communities for additional analysis, enhanced visualization, and communication of flood risks for hazard mitigation planning and emergency management. The Flood Depth and Analysis Grids provide an alternative way to visualize how a particular flood characteristic (depth, velocity, etc.) vary within the floodplain. Since they are derived from the engineering modeling results, they are typically associated with a particular frequency-based flooding event (e.g., 1% annual chance event). Grids provided in the FRD for this project area include the following:

- **Flood Depth Grids (for the calculated flood frequencies included in the FIS Report):** Flood Depth Grids are created for each flood frequency calculated during the course of a Flood Risk Project. These grids communicate flood depth as a function of the difference between the calculated water surface elevation and the ground. The

Depth grids form the basis for refined Hazus loss estimates (as presented in a table in Section 3 of this report) and are used to calculate potential flood losses for display on the FRM and for tabular presentation in this report. Depth grids may also be used for a variety of ad-hoc risk visualization and mitigation initiatives.



- **Percent Annual Chance of Flooding Grid:** This is a grid dataset that represents the percent annual chance of flooding for locations along a flooding source. This grid uses the five standard flood frequencies.
- **Percent 30-Year Chance of Flooding Grid:** This is a grid dataset that represents the estimated likelihood of flooding at least once within a 30-year period, which is the average lifespan for a home mortgage, for all locations within the extent of the 1-percent-annual-chance and 0.2-percent-annual-chance floodplain.

Grid data can be used to communicate the variability of floodplains, such as where floodplains are particularly deep or hazardous, where residual risks lie behind levees, and where losses may be great after a flood event. For mitigation planning, grid data can inform the hazard profile and vulnerability analysis (what is at risk for different frequencies) and can be used for preliminary benefit-cost analysis screening. For floodplain management, higher regulatory standards can be developed in higher hazard flood prone areas (i.e., 10-percent-chance floodplains or deep floodplains).

Grid data is stored in the FRD, and a list of available grid data is provided in the FRR. Visualizations of grids (maps) are not provided.

2.2.3 Estimated Flood Loss Information

Flood loss estimates provided in the FRR were developed using a FEMA flood loss estimation tool, Hazus. Originally developed for earthquake risk assessment, Hazus has evolved into a multi-hazard tool developed and distributed by FEMA that can provide loss estimates for floods, earthquakes, and hurricane winds. Hazus is a nationally accepted, consistent flood risk assessment tool to assist individuals and communities to create a more accurate picture of flood risk. Some benefits of using Hazus include the following:

- Outputs that can enhance state and local mitigation plans and help screen for cost-effectiveness in FEMA mitigation grant programs
- Analysis refinement through updating inventory data and integrating data produced using other flood models
- Widely available support documents and networks (Hazus Users Groups)

Files from the FRD can be imported into Hazus to develop other risk assessment information including:

- Debris generated after a flood event
- Dollar loss of the agricultural products in a study region
- Utility system damages in the region
- Vehicle loss in the study region



Hazus is a loss estimation methodology developed by FEMA for flood, wind, and earthquake hazards. The methodology and data established by Hazus can also be used to study other hazards.

- Damages and functionality of lifelines such as highway and rail bridges, potable water, and wastewater facilities

Scenario-Based Flood Loss Estimates:

Scenario-based flood losses have been calculated using Hazus for the 10-, 4-, 2-, 1-, and 0.2-percent-annual-chance flood events. In this report, these losses are expressed in dollar amounts and are provided for the Flood Risk Project area only.

Loss estimates are based on best available data, and the methodologies applied result in an approximation of risk. These estimates should be used to understand relative risk from flood and potential losses. Uncertainties are inherent in any loss estimation methodology, arising in part from approximations and simplifications that are necessary for a comprehensive analysis (e.g., incomplete inventories, demographics, or economic parameters).

Flood loss estimates are being provided at the project and community levels for multiple flood frequencies including:

- **Residential Asset Loss:** These include direct building losses (estimated costs to repair or replace the damage caused to the building) for all classes of residential structures including single family, multi-family, manufactured housing, group housing, and nursing homes. This value also includes content losses.
- **Commercial Asset Loss:** These include direct building losses for all classes of commercial buildings including retail, wholesale, repair, professional services, banks, hospitals, entertainment, and parking facilities. This value also includes content and inventory losses.
- **Other Asset Loss:** This includes losses for facilities categorized as industrial, agricultural, religious, government, and educational. This value also includes content and inventory losses.
- **Essential Facility Losses:** Essential facilities are defined in Hazus as facilities which provide services to the community and should be functional after a flood, including schools, police stations, fire stations, medical facilities, and emergency operation centers. These facilities would otherwise be considered critical facilities for mitigation planning purposes. Estimated damages (in terms of loss of function) for essential facilities are determined on a site-specific basis according to latitude and longitude. For this report, Hazus calculates the types and numbers of essential facilities impacted.
- **Infrastructure:** For analysis of infrastructure, Hazus supports the analysis of transportation systems and lifeline utility systems. Transportation systems include highways, railways, light railways, busses, ports and harbors, ferries, and airport systems. Utility systems include potable water systems, wastewater, oil, natural gas, electric power, and communication systems. For this report, Hazus calculates the types of infrastructure impacted.

Hazus-estimated loss data can be used in many ways to support local decision making and explanation of flood risk. For mitigation planning purposes, loss data can be used to help meet requirements to develop loss information for the hazard of flood. Also, the FRM can show where flood risk varies by geographic location. For emergency management, Hazus data can help forecast losses based on predicted events, and resources can be assigned accordingly. Loss information can support floodplain management efforts, including those to adopt higher regulatory standards. *Also, awareness of exposed essential facilities and infrastructure encourages mitigation actions to protect citizens from service disruption should flooding occur.*

Hazus estimated loss data is summarized in the FRR and on the FRM and stored in the FRD.

- **Business Disruption:** This includes the losses associated with the inability to operate a business due to the damage sustained during the flood. Losses include inventory, income, rental income, wage, and direct output losses, as well as relocation costs.
- **Annualized Losses:** Annualized losses are calculated using Hazus by taking losses from multiple events over different frequencies and expressing the long-term average by year. This factors in historic patterns of frequent smaller floods with infrequent but larger events to provide a balanced presentation of flood damage.
- **Loss Ratio:** The loss ratio expresses the scenario losses divided by the total building value for a local jurisdiction and can be a gage to determine overall community resilience as a result of a scenario event. For example, a loss ratio of 5 percent for a given scenario would indicate that a local jurisdiction would be more resilient and recover more easily from a given event, versus a loss ratio of 75 percent which would indicate widespread losses. An annualized loss ratio uses the annualized loss data as a basis for computing the ratio. Loss ratios are not computed for business disruption. These data are presented in the FRR.
- **Hazus Flood Risk Value:** On the FRM, flood risk is expressed in the following five categories: very low, low, medium, high, and very high for census blocks that have flood risk. It is based on the 1-percent-annual-chance total asset loss by census block.

2.2.4 Areas of Mitigation Interest

Many factors contribute to flooding and flood losses. Some are natural, and some are not. In response to these risks, there has been a focus by the federal government, state agencies, and local jurisdictions to mitigate properties against the impacts of flood hazards so that future losses and impacts can be reduced. An area identified as an Area of Mitigation Interest (AoMI) is an important element of defining a more comprehensive picture of flood risk and mitigation activity in a watershed, identifying target areas and potential projects for flood hazard mitigation, encouraging local collaboration, and communicating how various mitigation activities can successfully reduce flood risk.

This report and the FRM may include information that focuses on identifying Areas of Mitigation Interest that may be contributing (positively or negatively) to flooding and flood losses in the Flood Risk Project. AoMIs are identified through coordination with local stakeholders; through revised hydrologic and hydraulic and/or coastal analyses; by leveraging other studies or previous flood studies; from community mitigation plans, floodplain management plans, and local surveys; and from the mining of federal government databases (e.g., flood claims, disaster grants, and data from other agencies). Below is a list of the types of Areas of Mitigation Interest that may be identified in this Flood Risk Report, shown on the Flood Risk Map, and stored in the Flood Risk Database:

- **Dams**

A dam is a barrier built across a waterway for impounding water. Dams vary from impoundments that are hundreds of feet tall and contain thousands of acre-feet of water (e.g., Hoover Dam) to small dams that are a few feet high and contain only a few acre-feet of water (e.g., small residential pond). “Dry dams,” which are designed to contain water only during floods and do not impound water except for the purposes of flood control, include otherwise dry land behind the dam.

While most modern, large dams are highly engineered structures with components such as impervious cores and emergency spillways, most smaller and older dams are not. State dam safety programs emerged in the 1960s, and the first Federal Guidelines for Dam Safety were not prepared until 1979. By this time, the vast majority of dams in the United States had already been constructed.



Dams vary in size and shape, the amount of water they impound, and their assigned hazard classification.

O Reasons dams are considered AoMIs:

- Many older dams were not built to any particular standard and thus may not withstand extreme rainfall events. Older dams in some parts of the country are made out of an assortment of materials. These structures may not have any capacity to release water and could be overtopped, which could result in catastrophic failure.
- Even dams that follow current dam safety programs may not be regulated, as downstream risk may have changed since the dam was constructed. Years after a dam is built, a house, subdivision, or other development may be constructed in the dam failure inundation zone downstream of the dam. Thus, a subsequent dam failure could result in damage. Since these dams are not regulated, it is impossible to predict how safe they are.
- A significant dam failure risk is structural deficiencies associated with older dams that are not being adequately addressed today through needed inspection/maintenance practices.
- For larger dams a flood easement may have been obtained on a property upstream or downstream of the dam. However, there may have been buildings constructed in violation of the flood easement.
- When a new dam is constructed, the placement of such a large volume of material in a floodplain area (if that is the dam location) will displace flood waters and can alter how the watercourse flows. This can result in flooding upstream, downstream, or both.
- For many dams, the dam failure inundation zone is not known. Not having knowledge of these risk areas could lead to unprotected development in these zones.



This dam failure caused flooding that damaged several homes and vehicles.

• Levees and Major Embankments

FEMA defines a levee as “a man-made structure, usually an earthen embankment, designed and constructed in accordance with sound engineering practices to contain, control, or divert the flow of water so as to provide protection from temporary flooding.” Levees are sometimes referred to as

dikes. Soil used to construct a levee is compacted to make the levee as strong and stable as possible. To protect against erosion and scouring, levees can be covered with everything from grass and gravel to harder surfaces like stone (riprap), asphalt, or concrete.

Similar to dams, levees have not been regulated in terms of safety and design standards until relatively recently. Many older levees were constructed in a variety of ways, from a farmer piling dirt along a stream to prevent nuisance flooding to levees made out of old mining spoil material. As engineered structures, levees are designed to a certain height and can fail if a flood event is greater than anticipated.

A floodwall is a vertical wall that is built to provide protection from a flood in a similar manner as a levee. Typically made of concrete or steel, floodwalls often are erected in urban locations where there is not enough room for a levee. Floodwalls are sometimes constructed


on a levee crown to increase the levee's height.

Most new dams and levees are engineered to a certain design standard. If that design is exceeded, they could be overtopped and fail catastrophically, causing more damage than if the levee was not there in the first place. Few levees anywhere in the nation are built to more than a 1-percent-annual-chance flood protection rating, and the areas behind them are still at some risk for flooding. This threat is called residual risk. In some states, residual risk areas can extend up to 15 miles from a riverbank. Although the probability of flooding may be lower because a levee exists, risk is nonetheless still present. The American Society of Civil Engineers' publication "So, You Live Behind a Levee!" provides an in-depth explanation of levee and residual risk.

Major embankments, on the other hand, are rarely designed with any flood protection level in mind. Railroads, road abutments, and canals—especially in the Western United States—are not considered levees or dams and have issues such as unknown construction materials/methods. These embankments are not regulated from a flood risk standpoint.

o Reasons levees and major embankments are considered AoMIs:

- Like dams, many levees in the United States were constructed using unknown techniques and materials. These levees have a higher failure rate than those that have been designed to today's standards.
- A levee might not provide the flood risk reduction it once did as a result of flood risk changes over time. Flood risk can change due to a number of factors, including increased flood levels due to climate change or better estimates of flooding, development in the watershed increasing flood levels and settlement of the levee or floodwall, and sedimentation in the levee channel. Increased flood levels mean decreased flood protection. The lack of adequate maintenance over time will also reduce the capability of a levee to contain the flood levels for which it was originally designed.
- Given enough time, any levee will eventually be overtopped or damaged by a flood that exceeds the levee's capacity. Still, a widespread public perception of levees is that



For more information about the risks associated with living behind levees, consult the publication "So, You Live Behind a Levee!" published by the American Society of Civil Engineers at <http://content.asce.org/ASCELeveeGuide.html>

they will always provide protection. This perception may lead to not taking mitigation actions such as purchasing flood insurance.

- A levee is a system that can fail due to its weakest point, and therefore maintenance is critical. Many levees in the United States are poorly maintained or not maintained at all. Maintenance also includes maintaining the drainage systems behind the levees so they can keep the protected area dry.



- **Coastal Structures**

Coastal structures are used to “harden” the shoreline for a variety of purposes and include:

- Jetties: Structures constructed to direct currents or accommodate vessels.
- Groynes: Protective structures of stone or concrete that extend from shore into the water to prevent a beach from washing away.
- Sea walls: A form of hard and strong coastal defense constructed on the inland part of a coast to reduce the effects of strong waves.
- As the rate of sea level rise accelerates, an increase in coastal erosion is likely. We are now facing rapid sea level changes on a scale of decades. Higher sea levels could affect the coastal zone and accelerate coastal erosion and flooding in a variety of way, including greater shoreline retreat; increased coastal erosion rates; property destruction; and saltwater intrusion into bays, rivers, and underground water resources. In addition, a general elevation in the water table due to sea level rise will result.
- **Reasons coastal structures are considered AoMIs:**
 - While coastal structures or “hardening of the shoreline” may provide a temporary level of flood reduction for a very specific site, it also interrupts the dynamic processes of the littoral flow (flow along the coastline) which results in accelerated coastal erosion.
 - Erosion often occurs along beaches during storms, especially severe storms that stay offshore for days and result in ongoing battering of the shoreline through high wind and waves. As the beach erodes, vulnerable properties are placed at even greater risk to coastal flooding, storm surge, wave heights, wave run up, and coastal erosion.
 - Higher water tables associated with sea level rise could lead to the failure of septic systems and other drainage systems, such as storm drains, which need to be located at a certain elevation above the water table. Elevation of the water table would also affect the river drainage systems by affecting the rate of infiltration and increasing the amount of runoff which would, in turn, increase the risk of flooding.



Canal levee breaches as a result of Hurricane Katrina in New Orleans in 2005. Note damages can be more extensive due to high velocity flood flows than if the levee was not there.

- **Stream Flow Constrictions**

A stream flow constriction occurs when a human-made structure, such as a culvert or bridge, constricts the flow of a river or stream. The results of this constriction can be increased damage potential to the structure, an increase in velocity of flow through the structure, and the creation of significant ponding or backwater upstream of the structure. Regulatory standards regarding the proper opening size for a structure spanning a river or stream are not consistent and may be non-existent. Some local regulations require structures to pass a volume of water that corresponds to a certain size rain event; however, under sizing, these openings can result in flood damage to the structure itself. After a large flood event, it is not uncommon to have numerous bridges and culverts “washed out.”

- **Reasons stream flow constrictions are considered AoMIs:**

- Stream flow constrictions can back water up on property upstream of the structure if not designed properly.
 - These structures can accelerate the flow through the structure causing downstream erosion if not properly mitigated. This erosion can affect the structure itself, causing undermining and failure.
 - If the constriction is a bridge or culvert, it can get washed out causing an area to become isolated and potentially more difficult to evacuate.
 - Washed-out culverts and associated debris can wash downstream and cause additional constrictions.

- **At-Risk Essential Facilities**

Essential facilities, sometimes called “critical facilities,” are those whose impairment during a flood could cause significant problems to individuals or communities. For example, when a community’s wastewater treatment is flooded and shut down, not only do contaminants escape and flow into the floodwaters, but backflows of sewage can contaminate basements or other areas of the community. Similarly, when a facility such as a hospital is flooded, it can result in a significant hardship on the community not only during the event but long afterwards as well.

- **Reasons at-risk essential facilities are considered AoMIs:**

- Costly and specialized equipment may be damaged and need to be replaced.
 - Impairments to facilities such as fire stations may result in lengthy delays in responding and a focus on evacuating the facility itself.
 - Critical records and information stored at these facilities may be lost.

- **Past Flood Insurance Claims and Individual Assistance/Public Assistance Hotspots**

Assistance provided after flood events (flood insurance in any event and Individual Assistance [IA] or Public Assistance [PA] after declared disasters) occurs in flood affected areas. Understanding geographically where this assistance is being provided may indicate unique flood problems.

Flood insurance claims are not always equally distributed in a



Clusters of past flood insurance claims can show where there is a repetitive flood problem.

community. Although estimates indicate that 20 to 50 percent of structures in identified flood hazard areas have flood insurance, clusters of past claims may indicate where there is a flood problem. However, clusters of past claims and/or areas where there are high payments under FEMA's IA or PA Programs may indicate areas of significant flood hazard.

o Reasons past claim hotspots are considered AoMIs:

- A past claim hotspot may reflect an area of recent construction (large numbers of flood insurance policies as a result of a large number of mortgages) and an area where the as-built construction is not in accordance with local floodplain management regulations.
- Sometimes clusters of past claims occur in subdivisions that were constructed before flood protection standards were in place, places with inadequate stormwater management systems, or in areas that may not have been identified as SFHAs.
- Clusters of IA or PA claims may indicate areas where high flood insurance coverage or other mitigation actions are needed.

• Areas of Significant Land Use Change

Development, whether it is a 100-lot subdivision or a single lot big box commercial outlet, can result in large amounts of fill and other material being deposited in flood storage areas, thereby increasing flood hazards downstream.

Additionally, when development occurs, hard surfaces such as parking lots, buildings and driveways do not allow water to absorb into the ground, and more of the rainwater becomes runoff flowing directly into streams. As a result, the "peak flow" in a stream after a storm event will be higher and will occur faster. Without careful planning, major land use changes can affect the impervious area of a site and result in a significant increase in flood risk caused by streams that cannot handle the extra storm water runoff.

Changes in land use in areas vulnerable to coastal flooding may affect the severity of wave hazards. Wave energy dissipates as waves propagate through forested areas or areas with dense development while wave energy can increase in open areas such as agricultural fields or parking lots. Changes in land use can affect wave hazards beyond the immediate area of land use change.

Sometimes a major land use change may be for planning purposes only. For example, a land use change that rezones land from a classification such as floodplain that restricts development to a zone such as industrial or high density residential could result in significant new infrastructure and structures in high flood risk areas.



Rooftops, pavements, patios, and driveways contribute to the impervious area in a watershed. This occurs in both urban areas and rural areas being developed.

o Reasons Areas of Significant Land Use Change are considered AoMIs:

- Development in areas mapped SFHA reduces flood storage areas, which can make flooding worse at the development site and downstream of it.
- Impervious surfaces speed up the water flowing in the streams, which can increase erosion and the danger that fast-flowing floodwaters pose to people and buildings.
- Open areas can allow wave energy to increase while densely developed areas and dense vegetation cover often obstruct waves. These obstructions diminish the wave's potentially destructive forces in areas inland of the obstructions.
- Rezoning flood-prone areas to high densities and/or higher intensity uses can result in more people and property at risk of flooding and flood damage.



When large highways close due to flooding, traffic is detoured causing inconvenience and economic loss.

• Key Emergency Routes Overtopped During Frequent Flooding Events

Roads are not always elevated above estimated flood levels, and present a significant flood risk to motorists during flooding events. When alternate routes are available, risks may be reduced, including risks to life and economic loss.

o Reasons overtopped roads are considered AoMIs:

- Such areas, when identified, can be accounted for and incorporated into Emergency Action Plans.
- Roads may be elevated or reinforced to reduce the risk of overtopping during flood events.

• Drainage or Stormwater-Based Flood Hazard Areas, or Areas Not Identified as Floodprone on the FIRM But Known to Be Inundated

Flood hazard areas exist everywhere. While FEMA maps many of these, others are not identified. Many of these areas may be located in communities with existing, older, and often inadequate stormwater management systems or in very rural areas. Other similar areas could be a result of complex or unique drainage characteristics. Even though they are not mapped, awareness of these areas is important so adequate planning and mitigation actions can be performed.

o Reasons drainage or stormwater-based flood hazard areas or unidentified floodprone locations are considered AoMIs:

- So further investigation of such areas can occur and, based on scientific data, appropriate mitigation actions can result (i.e., land use and building standards).
- To create viable mitigation project applications in order to reduce flood losses.

- **Areas of Mitigation Success**

Flood mitigation projects are powerful tools to communicate the concepts of mitigation and result in more resilient communities. Multiple agencies have undertaken flood hazard mitigation actions for decades. Both structural measures—those that result in flood control structures—and non-structural measures have been implemented in thousands of communities. An extensive list of mitigation actions can be found in Section 4.

- **Reasons areas of mitigation success are considered AoMIs:**

- Mitigation successes identify those areas within the community that have experienced a reduction or elimination of flood risk.
 - Such areas are essential in demonstrating successful loss reduction measures and in educating citizens and officials on available flood hazard mitigation techniques.
 - Avoided losses can be calculated and shown.

- **Areas of Significant Riverine or Coastal Erosion**

Stream channels are shaped by a number of factors, including: degradation, aggradation, general scour, local scour, deposition, and lateral migration. Streams are constantly progressing towards a state of dynamic equilibrium involving water and sediment.

- **Reasons why areas of significant riverine or coastal erosion are considered AoMIs:**

- Riverine flood damage assessments generally consider inundation alone
 - Bank erosion caused by within channel flows is not recognized as a significant hazard in Federal floodplain management regulations
 - Riverine and coastal erosion can undercut structures and roads, causing instability and possible collapse.
 - Landslides and mudslides are a result of erosion
 - Approximately one-third of the nation's streams experience severe erosion problems

- **Other**

Other types of flood risk areas include drainage or stormwater-based flood hazard areas, or areas known to be inundated during storm events.

3 Flood Risk Analysis Results


The following pages provide summary flood risk results for the Flood Risk Project as follows:

- **Flood Risk Map (FRM).** Within the Flood Risk Project the FRM displays base data reflecting community boundaries, major roads, and stream lines; potential losses that include both the 2010 Average Annualized Loss (AAL) flood loss study supplemented with new Hazus runs for areas with new or updated flood modeling; new Flood Risk Project areas; a bar chart summarizing community per capita loss; and graphics and text that promote access and usage of additional data available through the FRD, FIRM, and National Flood Hazard Layer and viewers (desktop or FEMA website, etc.). This information can be used to assist in Flood Risk Project-level planning as well as for developing mitigation actions within each jurisdiction located within the Flood Risk Project.

The FRM provides a graphical overview of the Flood Risk Project which highlights areas of risk that should be noted, based on potential losses, exposed facilities, etc., based on data found in the FRD. Refer to the data in the FRD to conduct additional analyses.
- **Flood Risk Project Summary.** Within the Flood Risk Project area, summary data for some or all of the following datasets are provided for the entire project area and also on a jurisdiction by jurisdiction basis:
 - **Changes Since Last FIRM (CSLF).** This is a summary of where the floodplain and flood zones have increased or decreased (only analyzed for areas that were previously mapped using digital FIRMs).
 - **Flood Depth and Analysis Grids.** A general discussion of the data provided in the FRD, including coastal and dam analysis grids if furnished as part of the project.
 - **Flood Risk Assessment Information.** A loss estimation of potential flood damages using different flood scenarios.

3.1 Flood Risk Map

The Flood Risk Map for this Flood Risk Project is shown below. In addition to this reduced version of the map, a full size version is available within the FRD.



This page left intentionally blank.

3.2 Jefferson County Coastal Project Area Flood Risk Project Summary

Located on the Gulf Coast of Texas, Jefferson County covers approximately 1,230 square miles, approximately 792 of which are included in this Coastal Project Area. The coastline is characterized by a narrow, wave-cut beach and low ridges. A large portion of the area near the Gulf is coastal marshland. Elevations range from sea level along the coast to approximately 46 feet above sea level in the northwestern part of the county. Natural drainage is generally poor as many of the streams have shallow meandering channels. There is an extensive network of freshwater canals used for irrigation. Principal flooding problems include stream overflow caused by rainfall runoff, ponding, and sheet flow, and from tidal surges caused by hurricanes and tropical storms.

The Jefferson County Coastal Project includes grid and flood risk datasets based on two separate analyses. The first analysis is based on Stillwater data only, which includes storm surge and setup, and is referred to as the ADCIRC analysis. The ADCIRC data is a beneficial tool because it includes multiple return periods (10%-, 2%-, 1%-, and 0.2%-annual-chance-events) and allows for development of the probability grids. However, in areas of expected coastal wave effects for each respective return period, the ADCIRC datasets do not reflect the complete risk. The second analysis is a wave height study, which involves overland wave propagation, runup and overtopping as applicable, in addition to the Stillwater data, and is referred to as the WHAFIS analysis. The WHAFIS data represents the regulatory coastal flood zones as mapped in the FIRMs, but the analysis only includes the 1%-annual-chance-event.

3.2.1 Overview

The Jefferson County Coastal Project Area is located in Texas and includes the following communities:

Table 1. Overview of Project Area Communities

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Beaumont	485457	117,248	1.4	84.1	13.5	Y	8	Y
City of Groves	485475	17,582	0.2	5.2	<0.1	Y	N/A	Y
City of Nederland	485492	19,782	5.5	5.8	4.8	Y	N/A	Y
City of Port Arthur	485499	61,182	5.6	104	64.8	Y	9	Y
City of Port Neches	485500	14,161	7.7	9	27.7	Y	N/A	Y
City of Taylor Landing	481698	233	100	1.2	100	Y	N/A	Y
Jefferson County Unincorporated Areas	480385	40,180	36.2	1,019.7	69.6	Y	N/A	Y

Community-specific results are provided on subsequent pages. Data provided below and on subsequent pages only includes areas located within Jefferson County Coastal Project Area Flood Risk Project.

Section 2 of the Flood Risk Report provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project is described in Section 7 of the FRR and are found in the Flood Risk Database.

3.2.2 Flood Risk Datasets

As a part of this Flood Risk Project, flood risk datasets were created for inclusion in the Flood Risk Database. Those datasets are summarized for this Flood Risk Project below:

- **Changes Since Last FIRM**

- Special Flood Hazard Areas (SFHA) boundaries within the Jefferson County Coastal Project Area were updated due to new engineering analysis within the coastal project area. The updated modeling produced revised flood zone areas and new base flood elevations that leveraged new analysis performed by the U.S. Army Corps of Engineers (USACE) and FEMA. Section 2 of the FRR provides general information regarding the development of and potential uses for this data.

The table below summarizes the increases, decreases, and net change of SFHAs for the Jefferson County Coastal Project Area.

Table 2. Summary of Project Area SFHA Net Change

Area of Study	Total Area (mi ²)	Increase (mi ²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA*	713.7	36	18.1	18.6
Within Floodway**	N/A	N/A	N/A	N/A

**Although the Flood Risk Database may contain Changes Since Last FIRM information outside of project area, the figures in this table only represent information within the Jefferson County Coastal Project Area.*

*** Due to the lack of positional accuracy of the Effective Floodway data, please view any floodway changes directly on <http://www.txchart.com>. During this Risk MAP project, FEMA worked with the community to identify areas of potential mitigation and encourages the communities within the County to continue to work with the State of Texas to further identify and mitigate any high-risk areas and structures.*

- **Flood Depth and Analysis Grids**

- The FRD contains datasets in the form of depth grids for the entire Flood Risk Project that can be used for additional analysis, enhanced visualization, and communication of flood risks for hazard mitigation planning and emergency management. The data provided within the FRD should be used to further isolate areas where flood mitigation potential is high and may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation. Section 2 of the FRR provides general information regarding the development of and potential uses for this data.
- The ADCIRC depth grids are storm surge and setup (stillwater) depths only and do not include wave effects; as a result, these grids reflect depths less than would be expected

during a storm event and should be used with an understanding that they do not convey the full flood risk.

- o The WHAFIS depth grid includes the wave height analysis based on the ADCIRC storm surge results and is the basis for the regulatory coastal flood zones. The WHAFIS depth grid data corresponds to the mapped coastal special flood hazard zones on the FIRMs.

- **Flood Risk Results Information (Hazus Estimated Loss Information)**

- o Jefferson County Coastal Project Area's flood risk analysis incorporates results from a FEMA-performed Hazus analysis which accounts for average annualized loss (AAL) within the watershed. These data were entirely superseded for the coastally influenced areas within the Coastal Project Area for Jefferson County. FEMA's AAL results are included in the Flood Risk Database for general reference.
- o A Hazus "Level-2" analysis was performed only for the Coastal Project Area where updated FEMA and USACE engineering analysis resulted in revised flood hazard information. Both the Total Inventory of potential losses and the estimated loss results are calculated only for this project area and not for entire communities.
- o Two different datasets have been incorporated into the risk analyses; storm surge and setup only (ADCIRC) and the ADCIRC storm surge data with full wave analysis (WHAFIS). Specific to the ADCIRC analyses, multiple return period risk analyses has been performed to include the 10%-, 2%-, 1%-, and 0.2%-annual-chance hazard. Specific to the WHAFIS analyses, ONLY the 1%-annual-chance hazard analysis is included in this FRD. The ADCIRC and WHAFIS loss results are shown in separate tables and the ADCIRC results should be understood to not include wave effects.
- o WHAFIS wave run-up depths are higher than ADCIRC only depths for the 1%-annual-chance-hazard, resulting in higher estimated losses in areas covered by both grids. Please note that WHAFIS result tables are shown only for communities where the damage estimates showed a significant increase over 1%-annual-chance ADCIRC damage estimates.
- o The loss estimations for this Level-2 scenario utilize the General Building Stock data provided by the Texas Water Development Board (TWDB). The results may reflect the improved location of the SFHAs, improved topographic data, or may also demonstrate the effectiveness of flood protection measures, like levees, that have seen recent improvements. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

Table 3. Summary of Estimated Potential Losses

	Jefferson County Coastal Project Area Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	\$420,300,000	85%	\$6,500,000	1%	\$19,500,000	4%	\$40,600,000	8%	\$82,500,000	17%	\$2,000,000	<1%
Commercial Building and Contents	\$58,100,000	12%	\$3,200,000	<1%	\$7,200,000	1%	\$10,700,000	2%	\$18,800,000	4%	\$600,000	<1%
Other Building and Contents	\$18,300,000	3%	\$300,000	<1%	\$800,000	<1%	\$1,300,000	<1%	\$3,600,000	<1%	\$80,000	<1%
Total Building and Contents ²	\$496,700,000	100%	\$10,000,000	2%	\$27,500,000	6%	\$52,600,000	11%	\$104,900,000	21%	\$2,700,000	1%
Business Disruption ³	N/A	N/A	\$200,000	N/A	\$600,000	N/A	\$900,000	N/A	\$1,700,000	N/A	\$50,000	N/A
TOTAL⁴	\$496,700,000	N/A	\$10,200,000	2%	\$28,100,000	6%	\$53,500,000	11%	\$106,600,000	21%	\$2,800,000	1%

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Both total inventory and estimated losses are only for the coastal hazard areas of Jefferson County. Loss Ratios appear high because the area being included in the analysis is limited to only the Jefferson County Coastal Project Area.

A value of \$0 in the Potential Losses table may indicate some loss, but due to the rounding rules used to display the data and results, these show as a \$0.

Please note that WHAFIS result tables are shown only for communities where the damage estimates showed a significant increase over 1%-annual-chance ADCIRC damage estimates.

3.3 Communities

The following sections provide an overview of the community's floodplain management program as of the date of this publication, as well as summarize the flood risk analysis performed for the Jefferson County Coastal Project Area.

3.3.1 City of Beaumont (CID 485457)

The following pages include Flood Risk data for the City of Beaumont.

3.3.1.1 Overview

The information below provides an overview of City of Beaumont's floodplain management program information as of the date of this publication.

Table 5. Overview of Project Area Communities

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Beaumont	485457	117,248	1.4	84.1	13.5	Y	8	Y

- Participating in the Hazard Mitigation Action Plan for Jefferson County
- Past Federal Disaster Declarations for flooding =8
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = 8,393/\$2,271,666,200
- NFIP-recognized repetitive loss properties = 189
- NFIP-recognized severe repetitive loss properties = 11

Data provided below only includes areas within the City of Beaumont, and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.1.2 Community Analyses and Results

- **Changes Since Last FIRM**
 - Special Flood Hazard Area (SFHA) boundaries within the City of Beaumont were updated due to new engineering analysis performed within the Flood Risk Project. The updated modeling produced new flood zone areas and new base flood elevations in some areas and leveraged recently developed LiDAR-based topographic data for the Flood Risk Project. The data in this section reflects the comparison between the effective FIRM(s) and the new analysis in this study. Section 2 of the FRR provides general information regarding the development and potential uses for this data.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Table 6. Summary of Project Area SFHA Net Change

Area of Study	Total Area (mi ²)	Increase (mi ²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA*	40.1	0.2	0.6	0.4
Within Floodway**	N/A	N/A	N/A	N/A

**Although the Flood Risk Database may contain Changes Since Last FIRM information outside of project area, the figures in this table only represent information within the Jefferson County Coastal Project Area.*

*** Due to the lack of positional accuracy of the Effective Floodway data, please view any floodway changes directly on <http://www.txchart.com>. During this Risk MAP project, FEMA worked with the community to identify areas of potential mitigation and encourages the communities within the County to continue to work with the State of Texas to further identify and mitigate any high-risk areas and structures.*

- **Flood Depth and Analysis Grids**

- The FRD contains datasets in the form of depth grids for the entire Flood Risk Project that can be used for additional analysis, enhanced visualization, and communication of flood risks for hazard mitigation planning and emergency management. The data provided within the FRD should be used to further isolate areas where flood mitigation potential is high and may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation. Section 2 of the FRR provides general information regarding the development of and potential uses for this data.
- The ADCIRC depth grids are storm surge and setup (stillwater) depths only and do not include wave effects; as a result, these grids reflect depths less than would be expected during a storm event and should be used with an understanding that they do not convey the full flood risk.
- The WHAFIS depth grid includes the wave height analysis based on the ADCIRC storm surge results and is the basis for the regulatory coastal flood zones. The WHAFIS depth grid data corresponds to the mapped coastal special flood hazard zones on the FIRMs.

- **Flood Risk Results Information (Hazus Estimated Loss Information)**

- Jefferson County Coastal Project Area's flood risk analysis incorporates results from a FEMA-performed Hazus analysis which accounts for average annualized loss (AAL) within the watershed. These data were entirely superseded for the coastally influenced areas within the Coastal Project Area for Jefferson County. FEMA's AAL results are included in the Flood Risk Database for general reference.
- A Hazus "Level-2" analysis was performed only for the Coastal Project Area where updated FEMA and USACE engineering analysis resulted in revised flood hazard information. Both the Total Inventory of potential losses and the estimated loss results are calculated only for this project area and not for entire communities.
- Two different datasets have been incorporated into the risk analyses; storm surge and setup only (ADCIRC) and the ADCIRC storm surge data with full wave analysis (WHAFIS). Specific to the ADCIRC analyses, multiple return period risk analyses has been performed to include the 10%-, 2%-, 1%-, and 0.2%-annual-chance hazard. Specific to the WHAFIS analyses, ONLY the 1%-

annual-chance hazard analysis is included in this FRD. Please note that WHAFIS result tables are shown only for communities where the damage estimates showed a significant increase over 1%-annual-chance ADCIRC damage estimates.

- O The loss estimations for this Level-2 scenario utilize the General Building Stock data provided by the Texas Water Development Board (TWDB). The results may reflect the improved location of the SFHAs, improved topographic data, or may also demonstrate the effectiveness of flood protection measures, like levees, that have seen recent improvements. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

Table 7. Summary of Estimated Potential Losses

	City of Beaumont Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	\$13,700,000	76%	\$700,000	4%	\$1,000,000	6%	\$1,500,000	8%	\$2,300,000	13%	\$100,000	1%
Commercial Building and Contents	\$1,500,000	8%	\$70,000	<1%	\$70,000	<1%	\$100,000	1%	\$200,000	1%	\$10,000	<1%
Other Building and Contents	\$2,900,000	16%	\$50,000	<1%	\$80,000	<1%	\$100,000	1%	\$200,000	1%	\$10,000	<1%
Total Building and Contents ²	\$18,100,000	100%	\$800,000	5%	\$1,200,000	7%	\$1,700,000	9%	\$2,700,000	15%	\$100,000	1%
Business Disruption ³	\$0	N/A	\$10,000	N/A	\$10,000	N/A	\$20,000	N/A	\$40,000	N/A	\$0	N/A
TOTAL⁴	\$18,100,000	N/A	\$800,000	5%	\$1,200,000	7%	\$1,700,000	9%	\$2,700,000	15%	\$100,000	1%

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Both total inventory and estimated losses are only for the coastal hazard areas of Jefferson County. Loss Ratios appear high because the area being included in the analysis is limited to only the Jefferson County Coastal Project Area.

A value of \$0 in the Potential Losses table may indicate some loss, but due to the rounding rules used to display the data and results, these show as a \$0.

Please note that WHAFIS result tables are shown only for communities where the damage estimates showed a significant increase over 1%-annual-chance ADCIRC damage estimates.

3.3.2 City of Groves (CID 485475)

The following pages include Flood Risk data for the City of Groves.

3.3.2.1 Overview

The information below provides an overview of City of Groves' floodplain management program information as of the date of this publication.

Table 9. Overview of Project Area Communities

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Groves	485475	17,582	0.2	5.2	8.6	Y	N/A	Y

- Participating in the Hazard Mitigation Action Plan for Jefferson County
- Past Federal Disaster Declarations for flooding =8
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = 2,838/\$703,670,800
- NFIP-recognized repetitive loss properties = 27
- NFIP-recognized severe repetitive loss properties = 0

Data provided below only includes areas within the City of Groves, and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.2.2 Community Analyses and Results

- **Changes Since Last FIRM**
 - Special Flood Hazard Area (SFHA) boundaries within the City of Groves were updated due to new engineering analysis performed within the Flood Risk Project. The updated modeling produced new flood zone areas and new base flood elevations in some areas and leveraged recently developed LiDAR-based topographic data for the Flood Risk Project. The data in this section reflects the comparison between the effective FIRM(s) and the new analysis in this study. Section 2 of the FRR provides general information regarding the development and potential uses for this data.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Table 10. Summary of Project Area SFHA Net Change

Area of Study	Total Area (mi ²)	Increase (mi ²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA(*)(***)	N/A	N/A	N/A	N/A
Within Floodway**	N/A	N/A	N/A	N/A

**Although the Flood Risk Database may contain Changes Since Last FIRM information outside of project area, the figures in this table only represent information within the Jefferson County Coastal Project Area.*

*** Due to the lack of positional accuracy of the Effective Floodway data, please view any floodway changes directly on <http://www.txchart.com>. During this Risk MAP project, FEMA worked with the community to identify areas of potential mitigation and encourages the communities within the County to continue to work with the State of Texas to further identify and mitigate any high-risk areas and structures.*

****The City of Groves contains no Special Flood Hazard Area within the Jefferson County Coastal Project Area.*

- **Flood Depth and Analysis Grids**

- o The FRD contains datasets in the form of depth grids for the entire Flood Risk Project that can be used for additional analysis, enhanced visualization, and communication of flood risks for hazard mitigation planning and emergency management. The data provided within the FRD should be used to further isolate areas where flood mitigation potential is high and may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation. Section 2 of the FRR provides general information regarding the development of and potential uses for this data.
- o The ADCIRC depth grids are storm surge and setup (stillwater) depths only and do not include wave effects; as a result, these grids reflect depths less than would be expected during a storm event and should be used with an understanding that they do not convey the full flood risk.
- o The WHAFIS depth grid includes the wave height analysis based on the ADCIRC storm surge results and is the basis for the regulatory coastal flood zones. The WHAFIS depth grid data corresponds to the mapped coastal special flood hazard zones on the FIRMs.

- **Flood Risk Results Information (Hazus Estimated Loss Information)**

- o Jefferson County Coastal Project Area's flood risk analysis incorporates results from a FEMA-performed Hazus analysis which accounts for average annualized loss (AAL) within the watershed. These data were entirely superseded for the coastally influenced areas within the Coastal Project Area for Jefferson County. FEMA's AAL results are included in the Flood Risk Database for general reference.
- o A Hazus "Level-2" analysis was performed only for the Coastal Project Area where updated FEMA and USACE engineering analysis resulted in revised flood hazard information. Both the Total Inventory of potential losses and the estimated loss results are calculated only for this project area and not for entire communities.
- o Two different datasets have been incorporated into the risk analyses; storm surge and setup only (ADCIRC) and the ADCIRC storm surge data with full wave analysis (WHAFIS). Specific to the ADCIRC analyses, multiple return period risk analyses has been performed to include the 10%-,

2%-, 1%-, and 0.2%-annual-chance hazard. Specific to the WHAFIS analyses, ONLY the 1%-annual-chance hazard analysis is included in this FRD. The ADCIRC and WHAFIS loss results are shown in separate tables and the ADCIRC results should be understood to not include wave effects.

- O The loss estimations for this Level-2 scenario utilize the General Building Stock data provided by the Texas Water Development Board (TWDB). The results may reflect the improved location of the SFHAs, improved topographic data, or may also demonstrate the effectiveness of flood protection measures, like levees, that have seen recent improvements. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

Table 11. Summary of Estimated Potential Losses

	City of Groves Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Commercial Building and Contents	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Other Building and Contents	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Total Building and Contents ²	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Business Disruption ³	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
TOTAL⁴	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Because the City of Groves contains no Special Flood Hazard Area within the coastal project area, there is no Estimated Potential Losses information.

Table 12. Summary of Estimated Potential Losses (WHAFIS)

	City of Groves Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Commercial Building and Contents	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Other Building and Contents	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Total Building and Contents ²	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Business Disruption ³	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
TOTAL⁴	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Because the City of Groves contains no Special Flood Hazard Area within the coastal project area, there is no Estimated Potential Losses information.

3.3.3 City of Nederland (CID 485492)

The following pages include Flood Risk data for the City of Nederland.

3.3.3.1 Overview

The information below provides an overview of City of Nederland’s floodplain management program information as of the date of this publication.

Table 13. Overview of Project Area Communities

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Nederland	485492	19,782	5.5	5.8	4.8	Y	N/A	Y

- Participating in the Hazard Mitigation Action Plan for Jefferson County
- Past Federal Disaster Declarations for flooding =8
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = 2,804/\$715,940,700
- NFIP-recognized repetitive loss properties = 75
- NFIP-recognized severe repetitive loss properties = 3

Data provided below only includes areas within the City of Nederland, and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.3.2 Community Analyses and Results

- **Changes Since Last FIRM**
 - Special Flood Hazard Area (SFHA) boundaries within the City of Nederland were updated due to new engineering analysis performed within the Flood Risk Project. The updated modeling produced new flood zone areas and new base flood elevations in some areas and leveraged recently developed LiDAR-based topographic data for the Flood Risk Project. The data in this section reflects the comparison between the effective FIRM(s) and the new analysis in this study. Section 2 of the FRR provides general information regarding the development and potential uses for this data.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Table 14. Summary of Project Area SFHA Net Change

Area of Study	Total Area (mi ²)	Increase (mi ²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA*	0.2	0.1	0.1	0
Within Floodway**	N/A	N/A	N/A	N/A

**Although the Flood Risk Database may contain Changes Since Last FIRM information outside of project area, the figures in this table only represent information within the Jefferson County Coastal Project Area.*

*** Due to the lack of positional accuracy of the Effective Floodway data, please view any floodway changes directly on <http://www.txchart.com>. During this Risk MAP project, FEMA worked with the community to identify areas of potential mitigation and encourages the communities within the County to continue to work with the State of Texas to further identify and mitigate any high-risk areas and structures.*

- **Flood Depth and Analysis Grids**

- The FRD contains datasets in the form of depth grids for the entire Flood Risk Project that can be used for additional analysis, enhanced visualization, and communication of flood risks for hazard mitigation planning and emergency management. The data provided within the FRD should be used to further isolate areas where flood mitigation potential is high and may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation. Section 2 of the FRR provides general information regarding the development of and potential uses for this data.
- The ADCIRC depth grids are storm surge and setup (stillwater) depths only and do not include wave effects; as a result, these grids reflect depths less than would be expected during a storm event and should be used with an understanding that they do not convey the full flood risk.
- The WHAFIS depth grid includes the wave height analysis based on the ADCIRC storm surge results and is the basis for the regulatory coastal flood zones. The WHAFIS depth grid data corresponds to the mapped coastal special flood hazard zones on the FIRMs.

- **Flood Risk Results Information (Hazus Estimated Loss Information)**

- Jefferson County Coastal Project Area's flood risk analysis incorporates results from a FEMA-performed Hazus analysis which accounts for average annualized loss (AAL) within the watershed. These data were entirely superseded for the coastally influenced areas within the Coastal Project Area for Jefferson County. FEMA's AAL results are included in the Flood Risk Database for general reference.
- A Hazus "Level-2" analysis was performed only for the Coastal Project Area where updated FEMA and USACE engineering analysis resulted in revised flood hazard information. Both the Total Inventory of potential losses and the estimated loss results are calculated only for this project area and not for entire communities.
- Two different datasets have been incorporated into the risk analyses; storm surge and setup only (ADCIRC) and the ADCIRC storm surge data with full wave analysis (WHAFIS). Specific to the ADCIRC analyses, multiple return period risk analyses has been performed to include the 10%-, 2%-, 1%-, and 0.2%-annual-chance hazard. Specific to the WHAFIS analyses, ONLY the 1%-

annual-chance hazard analysis is included in this FRD. The ADCIRC and WHAFIS loss results are shown in separate tables and the ADCIRC results should be understood to not include wave effects.

- O The loss estimations for this Level-2 scenario utilize the General Building Stock data provided by the Texas Water Development Board (TWDB). The results may reflect the improved location of the SFHAs, improved topographic data, or may also demonstrate the effectiveness of flood protection measures, like levees, that have seen recent improvements. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

Table 15. Summary of Estimated Potential Losses

	City of Nederland Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	\$23,700,000	82%	N/A	N/A	N/A	N/A	N/A	N/A	\$3,000,000	10%	\$20,000	<1%
Commercial Building and Contents	\$5,000,000	18%	N/A	N/A	N/A	N/A	N/A	N/A	\$600,000	2%	\$0	N/A
Other Building and Contents	\$10,000	<1%	N/A	N/A	N/A	N/A	N/A	N/A	\$0	N/A	\$0	N/A
Total Building and Contents ²	\$28,700,000	100%	N/A	N/A	N/A	N/A	N/A	N/A	\$3,600,000	13%	\$20,000	<1%
Business Disruption ³	\$0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	\$40,000	N/A	\$0	N/A
TOTAL⁴	\$28,700,000	N/A	N/A	N/A	N/A	N/A	N/A	N/A	\$3,600,000	13%	\$20,000	<1%

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Both total inventory and estimated losses are only for the coastal hazard areas of Jefferson County. Loss Ratios appear high because the area being included in the analysis is limited to only the Jefferson County Coastal Project Area.

A value of \$0 in the Potential Losses table may indicate some loss, but due to the rounding rules used to display the data and results, these show as a \$0.

Table 16. Summary of Estimated Potential Losses (WHAFIS)

	City of Nederland Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	\$23,700,000	82%	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Commercial Building and Contents	\$5,000,000	18%	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Other Building and Contents	\$10,000	<1%	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Total Building and Contents ²	\$28,700,000	100%	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Business Disruption ³	\$0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
TOTAL⁴	\$28,700,000	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Because the City of Nederland does not contain the 1%-annual-chance flood hazard within the coastal project area, there is no WHAFIS information.

3.3.4 City of Port Arthur (CID 485499)

The following pages include Flood Risk data for the City of Port Arthur.

3.3.4.1 Overview

The information below provides an overview of City of Port Arthur's floodplain management program information as of the date of this publication.

Table 17. Overview of Project Area Communities

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Port Arthur	485499	61,182	5.6	104	64.8	Y	9	Y

- Participating in the Hazard Mitigation Action Plan for Jefferson County
- Past Federal Disaster Declarations for flooding =8
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = 6,250/\$1,447,578,100
- NFIP-recognized repetitive loss properties = 241
- NFIP-recognized severe repetitive loss properties = 7

Data provided below only includes areas within the City of Port Arthur, and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.4.2 Community Analyses and Results

- **Changes Since Last FIRM**
 - Special Flood Hazard Area (SFHA) boundaries within the City of Port Arthur were updated due to new engineering analysis performed within the Flood Risk Project. The updated modeling produced new flood zone areas and new base flood elevations in some areas and leveraged recently developed LiDAR-based topographic data for the Flood Risk Project. The data in this section reflects the comparison between the effective FIRM(s) and the new analysis in this study. Section 2 of the FRR provides general information regarding the development and potential uses for this data.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Table 18. Summary of Project Area SFHA Net Change

Area of Study	Total Area (mi ²)	Increase (mi ²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA*	74.7	18.7	3.3	15.6
Within Floodway**	N/A	N/A	N/A	N/A

**Although the Flood Risk Database may contain Changes Since Last FIRM information outside of project area, the figures in this table only represent information within the Jefferson County Coastal Project Area.*

*** Due to the lack of positional accuracy of the Effective Floodway data, please view any floodway changes directly on <http://www.txchart.com>. During this Risk MAP project, FEMA worked with the community to identify areas of potential mitigation and encourages the communities within the County to continue to work with the State of Texas to further identify and mitigate any high-risk areas and structures.*

- **Flood Depth and Analysis Grids**

- The FRD contains datasets in the form of depth grids for the entire Flood Risk Project that can be used for additional analysis, enhanced visualization, and communication of flood risks for hazard mitigation planning and emergency management. The data provided within the FRD should be used to further isolate areas where flood mitigation potential is high and may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation. Section 2 of the FRR provides general information regarding the development of and potential uses for this data.
- The ADCIRC depth grids are storm surge and setup (stillwater) depths only and do not include wave effects; as a result, these grids reflect depths less than would be expected during a storm event and should be used with an understanding that they do not convey the full flood risk.
- The WHAFIS depth grid includes the wave height analysis based on the ADCIRC storm surge results and is the basis for the regulatory coastal flood zones. The WHAFIS depth grid data corresponds to the mapped coastal special flood hazard zones on the FIRMs.

- **Flood Risk Results Information (Hazus Estimated Loss Information)**

- Jefferson County Coastal Project Area's flood risk analysis incorporates results from a FEMA-performed Hazus analysis which accounts for average annualized loss (AAL) within the watershed. These data were entirely superseded for the coastally influenced areas within the Coastal Project Area for Jefferson County. FEMA's AAL results are included in the Flood Risk Database for general reference.
- A Hazus "Level-2" analysis was performed only for the Coastal Project Area where updated FEMA and USACE engineering analysis resulted in revised flood hazard information. Both the Total Inventory of potential losses and the estimated loss results are calculated only for this project area and not for entire communities.
- Two different datasets have been incorporated into the risk analyses; storm surge and setup only (ADCIRC) and the ADCIRC storm surge data with full wave analysis (WHAFIS). Specific to the ADCIRC analyses, multiple return period risk analyses has been performed to include the 10%-, 2%-, 1%-, and 0.2%-annual-chance hazard. Specific to the WHAFIS analyses, ONLY the 1%-

annual-chance hazard analysis is included in this FRD. Please note that WHAFIS result tables are shown only for communities where the damage estimates showed a significant increase over 1%-annual-chance ADCIRC damage estimates.

- O The loss estimations for this Level-2 scenario utilize the General Building Stock data provided by the Texas Water Development Board (TWDB). The results may reflect the improved location of the SFHAs, improved topographic data, or may also demonstrate the effectiveness of flood protection measures, like levees, that have seen recent improvements. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

Table 19. Summary of Estimated Potential Losses

	City of Port Arthur Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	\$101,500,000	72%	\$3,500,000	2%	\$10,600,000	8%	\$22,100,000	16%	\$30,200,000	21%	\$1,000,000	1%
Commercial Building and Contents	\$35,200,000	25%	\$2,800,000	2%	\$6,200,000	4%	\$9,000,000	6%	\$13,900,000	10%	\$500,000	<1%
Other Building and Contents	\$4,200,000	3%	\$200,000	<1%	\$400,000	<1%	\$600,000	<1%	\$1,400,000	1%	\$40,000	<1%
Total Building and Contents ²	\$140,900,000	100%	\$6,500,000	5%	\$17,200,000	12%	\$31,700,000	22%	\$45,500,000	32%	\$1,500,000	1%
Business Disruption ³	\$0	N/A	\$200,000	N/A	\$400,000	N/A	\$600,000	N/A	\$1,000,000	N/A	\$40,000	N/A
TOTAL⁴	\$140,900,000	N/A	\$6,700,000	5%	\$17,600,000	13%	\$32,300,000	23%	\$46,500,000	33%	\$1,500,000	1%

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Both total inventory and estimated losses are only for the coastal hazard areas of Jefferson County. Loss Ratios appear high because the area being included in the analysis is limited to only the Jefferson County Coastal Project Area.

A value of \$0 in the Potential Losses table may indicate some loss, but due to the rounding rules used to display the data and results, these show as a \$0.

Please note that WHAFIS result tables are shown only for communities where the damage estimates showed a significant increase over 1%-annual-chance ADCIRC damage estimates.

3.3.5 City of Port Neches (CID 485500)

The following pages include Flood Risk data for the City of Port Neches.

3.3.5.1 Overview

The information below provides an overview of City Port Neches' floodplain management program information as of the date of this publication.

Table 21. Overview of Project Area Communities

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Port Neches	485500	14,161	7.7	9	27.7	Y	N/A	Y

- Participating in the Hazard Mitigation Action Plan for Jefferson County
- Past Federal Disaster Declarations for flooding =8
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = 2,373/\$668,898,200
- NFIP-recognized repetitive loss properties = 26
- NFIP-recognized severe repetitive loss properties = 0

Data provided below only includes areas within the City of Port Neches, and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.5.2 Community Analyses and Results

- **Changes Since Last FIRM**
 - Special Flood Hazard Area (SFHA) boundaries within the City of Port Neches were updated due to new engineering analysis performed within the Flood Risk Project. The updated modeling produced new flood zone areas and new base flood elevations in some areas and leveraged recently developed LiDAR-based topographic data for the Flood Risk Project. The data in this section reflects the comparison between the effective FIRM(s) and the new analysis in this study. Section 2 of the FRR provides general information regarding the development and potential uses for this data.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Table 22. Summary of Project Area SFHA Net Change

Area of Study	Total Area (mi ²)	Increase (mi ²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA*	9.4	0.5	0.1	0.4
Within Floodway**	N/A	N/A	N/A	N/A

**Although the Flood Risk Database may contain Changes Since Last FIRM information outside of project area, the figures in this table only represent information within the Jefferson County Coastal Project Area.*

*** Due to the lack of positional accuracy of the Effective Floodway data, please view any floodway changes directly on <http://www.txchart.com>. During this Risk MAP project, FEMA worked with the community to identify areas of potential mitigation and encourages the communities within the County to continue to work with the State of Texas to further identify and mitigate any high-risk areas and structures.*

- **Flood Depth and Analysis Grids**

- The FRD contains datasets in the form of depth grids for the entire Flood Risk Project that can be used for additional analysis, enhanced visualization, and communication of flood risks for hazard mitigation planning and emergency management. The data provided within the FRD should be used to further isolate areas where flood mitigation potential is high and may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation. Section 2 of the FRR provides general information regarding the development of and potential uses for this data.
- The ADCIRC depth grids are storm surge and setup (stillwater) depths only and do not include wave effects; as a result, these grids reflect depths less than would be expected during a storm event and should be used with an understanding that they do not convey the full flood risk.
- The WHAFIS depth grid includes the wave height analysis based on the ADCIRC storm surge results and is the basis for the regulatory coastal flood zones. The WHAFIS depth grid data corresponds to the mapped coastal special flood hazard zones on the FIRMs.

- **Flood Risk Results Information (Hazus Estimated Loss Information)**

- Jefferson County Coastal Project Area's flood risk analysis incorporates results from a FEMA-performed Hazus analysis which accounts for average annualized loss (AAL) within the watershed. These data were entirely superseded for the coastally influenced areas within the Coastal Project Area for Jefferson County. FEMA's AAL results are included in the Flood Risk Database for general reference.
- A Hazus "Level-2" analysis was performed only for the Coastal Project Area where updated FEMA and USACE engineering analysis resulted in revised flood hazard information. Both the Total Inventory of potential losses and the estimated loss results are calculated only for this project area and not for entire communities.
- Two different datasets have been incorporated into the risk analyses; storm surge and setup only (ADCIRC) and the ADCIRC storm surge data with full wave analysis (WHAFIS). Specific to the ADCIRC analyses, multiple return period risk analyses has been performed to include the 10%-, 2%-, 1%-, and 0.2%-annual-chance hazard. Specific to the WHAFIS analyses, ONLY the 1%-

annual-chance hazard analysis is included in this FRD. The ADCIRC and WHAFIS loss results are shown in separate tables and the ADCIRC results should be understood to not include wave effects.

- O The loss estimations for this Level-2 scenario utilize the General Building Stock data provided by the Texas Water Development Board (TWDB). The results may reflect the improved location of the SFHAs, improved topographic data, or may also demonstrate the effectiveness of flood protection measures, like levees, that have seen recent improvements. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

Table 23. Summary of Estimated Potential Losses

	City of Port Neches Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	\$22,900,000	95%	\$300,000	1%	\$600,000	2%	\$900,000	4%	\$2,300,000	9%	\$60,000	<1%
Commercial Building and Contents	\$1,300,000	5%	\$40,000	<1%	\$100,000	<1%	\$200,000	1%	\$300,000	1%	\$10,000	<1%
Other Building and Contents	\$0	N/A	\$0	N/A	\$0	N/A	\$0	N/A	\$0	N/A	\$0	N/A
Total Building and Contents ²	\$24,200,000	100%	\$300,000	1%	\$700,000	3%	\$1,100,000	5%	\$2,600,000	10%	\$70,000	<1%
Business Disruption ³	\$0	N/A	\$0	N/A	\$10,000	N/A	\$10,000	N/A	\$10,000	N/A	\$0	N/A
TOTAL⁴	\$24,200,000	N/A	\$300,000	1%	\$700,000	3%	\$1,100,000	5%	\$2,600,000	10%	\$70,000	<1%

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Both total inventory and estimated losses are only for the coastal hazard areas of Jefferson County. Loss Ratios appear high because the area being included in the analysis is limited to only the Jefferson County Coastal Project Area.

A value of \$0 in the Potential Losses table may indicate some loss, but due to the rounding rules used to display the data and results, these show as a \$0.

Table 24. Summary of Estimated Potential Losses (WHAFIS)

	City of Port Neches Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	\$22,900,000	95%	N/A	N/A	N/A	N/A	\$1,000,000	4%	N/A	N/A	N/A	N/A
Commercial Building and Contents	\$1,300,000	5%	N/A	N/A	N/A	N/A	\$200,000	1%	N/A	N/A	N/A	N/A
Other Building and Contents	\$0	N/A	N/A	N/A	N/A	N/A	\$0	N/A	N/A	N/A	N/A	N/A
Total Building and Contents ²	\$24,200,000	100%	N/A	N/A	N/A	N/A	\$1,200,000	5%	N/A	N/A	N/A	N/A
Business Disruption ³	\$0	N/A	N/A	N/A	N/A	N/A	\$10,000	N/A	N/A	N/A	N/A	N/A
TOTAL⁴	\$24,200,000	N/A	N/A	N/A	N/A	N/A	\$1,200,000	5%	N/A	N/A	N/A	N/A

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Both total inventory and estimated losses are only for the coastal hazard areas of Jefferson County. Loss Ratios appear high because the area being included in the analysis is limited to only the Jefferson County Coastal Project Area.

The WHAFIS results are only available for the 1%-annual-chance event and match the areas of wave analysis shown on the Flood Insurance Rate Maps for this community. WHAFIS wave run-up depths are higher than ADCIRC only depths resulting in higher estimated losses.

A value of \$0 in the Potential Losses table may indicate some loss, but due to the rounding rules used to display the data and results, these show as a \$0.

3.3.6 City of Taylor Landing (CID 481698)

The following pages include Flood Risk data for the City of Taylor Landing.

3.3.6.1 Overview

The information below provides an overview of City of Taylor Landing's floodplain management program information as of the date of this publication.

Table 25. Overview of Project Area Communities

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
City of Taylor Landing	481698	233	100	1.2	100	Y	N/A	Y

- Participating in the Hazard Mitigation Action Plan for Jefferson County
- Past Federal Disaster Declarations for flooding =8
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = 10/\$2,610,200
- NFIP-recognized repetitive loss properties = N/A
- NFIP-recognized severe repetitive loss properties = N/A

Data provided below only includes areas within the City of Taylor Landing, and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.6.2 Community Analyses and Results

- **Changes Since Last FIRM**
 - Special Flood Hazard Area (SFHA) boundaries within the City of Taylor Landing were updated due to new engineering analysis performed within the Flood Risk Project. The updated modeling produced new flood zone areas and new base flood elevations in some areas and leveraged recently developed LiDAR-based topographic data for the Flood Risk Project. The data in this section reflects the comparison between the effective FIRM(s) and the new analysis in this study. Section 2 of the FRR provides general information regarding the development and potential uses for this data.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Table 26. Summary of Project Area SFHA Net Change

Area of Study	Total Area (mi ²)	Increase (mi ²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA*	0.6	0	0.1	0.1
Within Floodway**	N/A	N/A	N/A	N/A

**Although the Flood Risk Database may contain Changes Since Last FIRM information outside of project area, the figures in this table only represent information within the Jefferson County Coastal Project Area.*

*** Due to the lack of positional accuracy of the Effective Floodway data, please view any floodway changes directly on <http://www.txchart.com>. During this Risk MAP project, FEMA worked with the community to identify areas of potential mitigation and encourages the communities within the County to continue to work with the State of Texas to further identify and mitigate any high-risk areas and structures.*

- **Flood Depth and Analysis Grids**

- The FRD contains datasets in the form of depth grids for the entire Flood Risk Project that can be used for additional analysis, enhanced visualization, and communication of flood risks for hazard mitigation planning and emergency management. The data provided within the FRD should be used to further isolate areas where flood mitigation potential is high and may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation. Section 2 of the FRR provides general information regarding the development of and potential uses for this data.
- The ADCIRC depth grids are storm surge and setup (stillwater) depths only and do not include wave effects; as a result, these grids reflect depths less than would be expected during a storm event and should be used with an understanding that they do not convey the full flood risk.
- The WHAFIS depth grid includes the wave height analysis based on the ADCIRC storm surge results and is the basis for the regulatory coastal flood zones. The WHAFIS depth grid data corresponds to the mapped coastal special flood hazard zones on the FIRMs.

- **Flood Risk Results Information (Hazus Estimated Loss Information)**

- Jefferson County Coastal Project Area's flood risk analysis incorporates results from a FEMA-performed Hazus analysis which accounts for average annualized loss (AAL) within the watershed. These data were entirely superseded for the coastally influenced areas within the Coastal Project Area for Jefferson County. FEMA's AAL results are included in the Flood Risk Database for general reference.
- A Hazus "Level-2" analysis was performed only for the Coastal Project Area where updated FEMA and USACE engineering analysis resulted in revised flood hazard information. Both the Total Inventory of potential losses and the estimated loss results are calculated only for this project area and not for entire communities.
- Two different datasets have been incorporated into the risk analyses; storm surge and setup only (ADCIRC) and the ADCIRC storm surge data with full wave analysis (WHAFIS). Specific to the ADCIRC analyses, multiple return period risk analyses has been performed to include the 10%-, 2%-, 1%-, and 0.2%-annual-chance hazard. Specific to the WHAFIS analyses, ONLY the 1%-

annual-chance hazard analysis is included in this FRD. The ADCIRC and WHAFIS loss results are shown in separate tables and the ADCIRC results should be understood to not include wave effects.

- O The loss estimations for this Level-2 scenario utilize the General Building Stock data provided by the Texas Water Development Board (TWDB). The results may reflect the improved location of the SFHAs, improved topographic data, or may also demonstrate the effectiveness of flood protection measures, like levees, that have seen recent improvements. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

Table 27. Summary of Estimated Potential Losses

	City of Taylor Landing Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	\$14,300,000	100%	\$200,000	1%	\$600,000	4%	\$1,200,000	9%	\$2,600,000	18%	\$60,000	<1%
Commercial Building and Contents	\$0	N/A	\$0	N/A	\$0	N/A	\$0	N/A	\$0	N/A	\$0	N/A
Other Building and Contents	\$0	N/A	\$0	N/A	\$0	N/A	\$0	N/A	\$0	N/A	\$0	N/A
Total Building and Contents ²	\$14,300,000	100%	\$200,000	1%	\$600,000	4%	\$1,200,000	9%	\$2,600,000	18%	\$60,000	<1%
Business Disruption ³	\$0	N/A	\$0	N/A	\$0	N/A	\$0	N/A	\$10,000	N/A	\$0	N/A
TOTAL⁴	\$14,300,000	N/A	\$200,000	1%	\$600,000	4%	\$1,200,000	9%	\$2,600,000	18%	\$60,000	<1%

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Both total inventory and estimated losses are only for the coastal hazard areas of Jefferson County. Loss Ratios appear high because the area being included in the analysis is limited to only the Jefferson County Coastal Project Area.

A value of \$0 in the Potential Losses table may indicate some loss, but due to the rounding rules used to display the data and results, these show as \$0.

Table 28. Summary of Estimated Potential Losses (WHAFIS)

	City of Taylor Landing Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	\$14,300,000	100%	N/A	N/A	N/A	N/A	\$1,300,000	9%	N/A	N/A	N/A	N/A
Commercial Building and Contents	\$0	N/A	N/A	N/A	N/A	N/A	\$0	N/A	N/A	N/A	N/A	N/A
Other Building and Contents	\$0	N/A	N/A	N/A	N/A	N/A	\$0	N/A	N/A	N/A	N/A	N/A
Total Building and Contents ²	\$14,300,000	100%	N/A	N/A	N/A	N/A	\$1,300,000	9%	N/A	N/A	N/A	N/A
Business Disruption ³	\$0	N/A	N/A	N/A	N/A	N/A	\$0	N/A	N/A	N/A	N/A	N/A
TOTAL⁴	\$14,300,000	N/A	N/A	N/A	N/A	N/A	\$1,300,000	9%	N/A	N/A	N/A	N/A

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Both total inventory and estimated losses are only for the coastal hazard areas of Jefferson County. Loss Ratios appear high because the area being included in the analysis is limited to only the Jefferson County Coastal Project Area.

The WHAFIS results are only available for the 1%-annual-chance event and match the areas of wave analysis shown on the Flood Insurance Rate Maps for this community. WHAFIS wave run-up depths are higher than ADCIRC only depths resulting in higher estimated losses.

A value of \$0 in the Potential Losses table may indicate some loss, but due to the rounding rules used to display the data and results, these show as \$0.

3.3.7 Jefferson County Unincorporated Areas (CID 480385)

The following pages include Flood Risk data for the Jefferson County Unincorporated Areas.

3.3.7.1 Overview

The information below provides an overview of Jefferson County Unincorporated Areas' floodplain management program information as of the date of this publication.

Table 29. Overview of Project Area Communities

Community Name	CID	Total Community Population	Percent of Population in Project Area	Total Community Land Area (sq mi)	Percent of Land Area in Project Area	NFIP	CRS Rating	Mitigation Plan
Jefferson County Unincorporated Areas	480385	40,180	36.2	1019.7	69.6	Y	N/A	Y

- Participating in the Hazard Mitigation Action Plan for Jefferson County
- Past Federal Disaster Declarations for flooding =8
- National Flood Insurance Program (NFIP) policy coverage (policies/value) = 2,851/\$789,062,000
- NFIP-recognized repetitive loss properties = 89
- NFIP-recognized severe repetitive loss properties = 7

Data provided below only includes areas within the Jefferson County Unincorporated Areas, and do not necessarily represent community-wide totals. Section 2 of the Flood Risk Report (FRR) provides more information regarding the source and methodology used to develop the information presented below. Datasets used toward the generation of results of this project are described in Section 7 of the FRR and are found in the Flood Risk Database (FRD).

3.3.7.2 Community Analyses and Results

- **Changes Since Last FIRM**
 - Special Flood Hazard Area (SFHA) boundaries within the Jefferson County Unincorporated Areas were updated due to new engineering analysis performed within the Flood Risk Project. The updated modeling produced new flood zone areas and new base flood elevations in some areas and leveraged recently developed LiDAR-based topographic data for the Flood Risk Project. The data in this section reflects the comparison between the effective FIRM(s) and the new analysis in this study. Section 2 of the FRR provides general information regarding the development and potential uses for this data.

The table below summarizes the increases, decreases, and net change of SFHAs for the community.

Table 30. Summary of Project Area SFHA Net Change

Area of Study	Total Area (mi ²)	Increase (mi ²)	Decrease (mi ²)	Net Change (mi ²)
Within SFHA*	588.7	16.5	13.9	3.1
Within Floodway**	N/A	N/A	N/A	N/A

**Although the Flood Risk Database may contain Changes Since Last FIRM information outside of project area, the figures in this table only represent information within the Jefferson County Coastal Project Area.*

*** Due to the lack of positional accuracy of the Effective Floodway data, please view any floodway changes directly on <http://www.txchart.com>. During this Risk MAP project, FEMA worked with the community to identify areas of potential mitigation and encourages the communities within the County to continue to work with the State of Texas to further identify and mitigate any high-risk areas and structures.*

- **Flood Depth and Analysis Grids**

- The FRD contains datasets in the form of depth grids for the entire Flood Risk Project that can be used for additional analysis, enhanced visualization, and communication of flood risks for hazard mitigation planning and emergency management. The data provided within the FRD should be used to further isolate areas where flood mitigation potential is high and may be helpful in planning and implementing mitigation strategies. Properties located in areas expected to experience some depth of water should seriously consider mitigation options for implementation. Section 2 of the FRR provides general information regarding the development of and potential uses for this data.
- The ADCIRC depth grids are storm surge and setup (stillwater) depths only and do not include wave effects; as a result, these grids reflect depths less than would be expected during a storm event and should be used with an understanding that they do not convey the full flood risk.
- The WHAFIS depth grid includes the wave height analysis based on the ADCIRC storm surge results and is the basis for the regulatory coastal flood zones. The WHAFIS depth grid data corresponds to the mapped coastal special flood hazard zones on the FIRMs.

- **Flood Risk Results Information (Hazus Estimated Loss Information)**

- Jefferson County Coastal Project Area's flood risk analysis incorporates results from a FEMA-performed Hazus analysis which accounts for average annualized loss (AAL) within the watershed. These data were entirely superseded for the coastally influenced areas within the Coastal Project Area for Jefferson County. FEMA's AAL results are included in the Flood Risk Database for general reference.
- A Hazus "Level-2" analysis was performed only for the Coastal Project Area where updated FEMA and USACE engineering analysis resulted in revised flood hazard information. Both the Total Inventory of potential losses and the estimated loss results are calculated only for this project area and not for entire communities.
- Two different datasets have been incorporated into the risk analyses; storm surge and setup only (ADCIRC) and the ADCIRC storm surge data with full wave analysis (WHAFIS). Specific to the

ADCIRC analyses, multiple return period risk analyses has been performed to include the 10%-, 2%-, 1%-, and 0.2%-annual-chance hazard. Specific to the WHAFIS analyses, ONLY the 1%-annual-chance hazard analysis is included in this FRD. Please note that WHAFIS result tables are shown only for communities where the damage estimates showed a significant increase over 1%-annual-chance ADCIRC damage estimates.

- o The loss estimations for this Level-2 scenario utilize the General Building Stock data provided by the Texas Water Development Board (TWDB). The results may reflect the improved location of the SFHAs, improved topographic data, or may also demonstrate the effectiveness of flood protection measures, like levees, that have seen recent improvements. Additional information and data layers provided within the FRD should be used to further analyze potential losses and areas where they are likely to occur.

Table 31. Summary of Estimated Potential Losses

	Jefferson County Unincorporated Areas Estimated Potential Losses for Flood Event Scenarios											
	Total Inventory		10% (10-yr)		2% (50-yr)		1% (100-yr)		0.2% (500-yr)		Annualized (\$/yr)	
	Estimated Value	% of Total	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}	Dollar Losses ⁵	Loss Ratio ^{1,6}
Residential Building and Contents	\$244,400,000	90%	\$1,900,000	1%	\$6,700,000	2%	\$14,900,000	6%	\$42,200,000	16%	\$800,000	<1%
Commercial Building and Contents	\$15,100,000	6%	\$300,000	<1%	\$800,000	<1%	\$1,400,000	1%	\$3,700,000	1%	\$80,000	<1%
Other Building and Contents	\$11,200,000	4%	\$80,000	<1%	\$300,000	<1%	\$600,000	<1%	\$2,000,000	1%	\$30,000	<1%
Total Building and Contents ²	\$270,700,000	100%	\$2,300,000	1%	\$7,800,000	3%	\$16,900,000	6%	\$47,900,000	18%	\$900,000	<1%
Business Disruption ³	\$0	N/A	\$30,000	N/A	\$100,000	N/A	\$200,000	N/A	\$500,000	N/A	\$10,000	N/A
TOTAL⁴	\$270,700,000	N/A	\$2,300,000	1%	\$7,900,000	3%	\$17,100,000	6%	\$48,400,000	18%	\$900,000	<1%

Source: HAZUS analysis results stored as the Flood Risk Assessment Dataset in the Flood Risk Database.

¹Loss ratio = Dollar Losses ÷ Estimated Value

²Total Building and Contents Loss = (Residential Building+Contents Loss) + (Commercial Building+Contents Loss) + (Other Building+Contents Loss).

³Business Disruption = Inventory Loss + Relocation Cost + Income Loss + Rental Income Loss + Wage Loss + Direct Output Loss.

⁴Total Loss = (Total Building+Contents) + Business Disruption

⁵Losses shown are rounded to nearest \$10,000 for values under \$100,000 and to the nearest \$100,000 for values over \$100,000.

⁶Loss Ratios rounded to nearest integer percent.

NOTE: Both total inventory and estimated losses are only for the coastal hazard areas of Jefferson County. Loss Ratios appear high because the area being included in the analysis is limited to only the Jefferson County Coastal Project Area.

A value of \$0 in the Potential Losses table may indicate some loss, but due to the rounding rules used to display the data and results, these show as \$0.

Please note that WHAFIS result tables are shown only for communities where the damage estimates showed a significant increase over 1%-annual-chance ADCIRC damage estimates.

4 Actions to Reduce Flood Risk

In order to fully leverage the Flood Risk Datasets and Products created for this Flood Risk Project, local stakeholders should consider many different flood risk mitigation tactics, including, but not limited to the items shown in the sub-sections below.

4.1 Types of Mitigation Actions

Mitigation provides a critical foundation on which to reduce loss of life and property by avoiding or lessening the impact of hazard events. This creates safer communities and facilitates resiliency by enabling communities to return to normal function as quickly as possible after a hazard event. Once a community understands its flood risk, it is in a better position to identify potential mitigation actions that can reduce the risk to its people and property.

The mitigation plan requirements in 44 CFR Part 201 encourage communities to understand their vulnerability to hazards and take actions to minimize vulnerability and promote resilience. Flood mitigation actions generally fall into the following categories:

4.1.1 Preventative Measures

Preventative measures are intended to keep flood hazards from getting worse. They can reduce future vulnerability to flooding, especially in areas where development has not yet occurred or where capital improvements have not been substantial. Examples include:

- Comprehensive land use planning
- Zoning regulations
- Subdivision regulations
- Open space preservation
- Building codes
- Floodplain development regulations
- Stormwater management
- Purchase development rights or conservation easements
- Participation in the NFIP Community Rating System (CRS)

Before Mitigation and After Mitigation



Communities will need to prioritize projects as part of the planning process. FEMA can then help route federal mitigation dollars to fund these projects.

NFIP's CRS is a voluntary incentive program that recognizes and encourages community floodplain management activities that exceed the minimum NFIP requirements. As a result, flood insurance premium rates are discounted to reflect the reduced flood risk resulting from community actions meeting the three goals of the CRS: to reduce flood losses, to facilitate accurate insurance rating, and to promote the awareness of flood insurance.

For CRS participating communities, flood insurance premium rates are discounted in increments of 5%; i.e., a Class 1 community would receive a 45% premium discount, while a Class 9

4.1.2 Property Protection Measures

Property protection measures protect existing buildings by modifying the building to withstand floods, or by removing buildings from hazardous locations. Examples include:

- Building relocation
- Acquisition and clearance
- Building elevation
- Barrier installation
- Building retrofit

4.1.3 Natural Resource Protection Activities

Natural resource protection activities reduce the impact of floods by preserving or restoring natural areas such as floodplains, wetlands, and dunes and their natural functions. Examples include:

- Wetland protection
- Habitat protection
- Erosion and sedimentation control
- Best management practices (BMP)
- Prevention of stream dumping activities (anti-litter campaigns)
- Improved forestry practices such as reforestation or selective timbering (extraction)

4.1.4 Structural Mitigation Projects

Structural mitigation projects lessen the impact of floods by modifying the environmental natural progression of the flooding event. Structural protection such as upgrading dams/levees for already existing development and critical facilities may be a realistic alternative. However, citizens should be made aware of their residual risk. Examples include:

- Reservoirs, retention, and detention basins
- Levees and floodwalls
- Channel modifications
- Channel maintenance

4.1.5 Public Education and Awareness Activities

Public education and awareness activities advise residents, business owners, potential property buyers, and visitors about floods, hazardous areas, and mitigation techniques they can use to reduce the flood risk to themselves and their property. Examples include:

- Readily available and readable updated maps
- Outreach projects

For more information regarding hazard mitigation techniques, best practices, and potential grant funding sources, visit www.fema.gov or contact your local floodplain manager, emergency manager, or State Hazard Mitigation Officer.

- Libraries
- Technical assistance
- Real estate disclosure
- Environmental education
- Risk information via the nightly news

4.1.6 Emergency Service Measures

Although not typically considered a mitigation technique, emergency service measures minimize the impact of flooding on people and property. These are actions commonly taken immediately prior to, during, or in response to a hazard event. Examples include:

- Hazard warning system
- Emergency response plan
- COOP and COG planning
- Critical facilities protection
- Health and safety maintenance
- Post flood recovery planning

4.2 Identifying Specific Actions for Your Community

As many mitigation actions are possible to lessen the impact of floods, how can a community decide which ones are appropriate to implement? There are many ways to identify specific actions most appropriate for a community. Some factors to consider may include the following:

- **Site characteristics.** Does the site present unique challenges (e.g., significant slopes or erosion potential)?
- **Flood characteristics.** Are the flood waters affecting the site fast or slow moving? Is there debris associated with the flow? How deep is the flooding?
- **Social acceptance.** Will the mitigation action be acceptable to the public? Does it cause social or cultural problems?
- **Technical feasibility.** Is the mitigation action technically feasible (e.g., making a building watertight to a reasonable depth)?
- **Administrative feasibility.** Is there administrative capability to implement the mitigation action?

Refer to FEMA Mitigation Planning How To Guide #3 (FEMA 386-3) "Developing the Mitigation Plan - Identifying Mitigation Actions and Implementation Strategies" for more information on how to identify specific mitigation actions to address hazard risk in your community.

- **Legal.** Does the mitigation action meet all applicable codes, regulations, and laws? Public officials may have a legal responsibility to act and inform citizens if a known hazard has been identified.
- **Economic.** Is the mitigation action affordable? Is it eligible under grant or other funding programs? Can it be completed within existing budgets?
- **Environmental.** Does the mitigation action cause adverse impacts on the environment or can they be mitigated? Is it the most appropriate action among the possible alternatives?

FEMA in collaboration with the American Planning Association has released the publication, "Integrating Hazard Mitigation into Local Planning." This guide explains how hazard mitigation can be incorporated into several different types of local planning programs. For more information go to www.planning.org. or <http://www.fema.gov/library>.

Your local Hazard Mitigation Plan is a valuable place to identify and prioritize possible mitigation actions. The plan includes a mitigation strategy with mitigation actions that were developed through a public and open process. You can then add to or modify those actions based on what is learned during the course of the Risk MAP project and the information provided within this FRR.

4.3 Mitigation Programs and Assistance

Not all mitigation activities require funding (e.g., local policy actions such as strengthening a flood damage prevention ordinance), and those that do are not limited to outside funding sources (e.g., inclusion in local capital improvements plan, etc.). For those mitigation actions that require assistance through funding or technical expertise, several state and federal agencies have flood hazard mitigation grant programs and offer technical assistance. These programs may be funded at different levels over time or may be activated under special circumstances such as after a presidential disaster declaration.



Communities can link hazard mitigation plans and actions to the right FEMA grant programs to fund flood risk reduction. More information about FEMA HMA programs can be found at <http://www.fema.gov/government/grant/hma/index.shtm>.

4.3.1 FEMA Mitigation Programs and Assistance

FEMA awards many mitigation grants each year to states and communities to undertake mitigation projects to prevent future loss of life and property resulting from hazard impacts, including flooding. The FEMA Hazard Mitigation Assistance (HMA) programs provide grants for mitigation through the programs listed in Table 9 below.

Table 9. FEMA Hazard Mitigation Assistance Programs

Mitigation Grant Program	Authorization	Purpose
Hazard Mitigation Grant Program (HMGP)	Robert T. Stafford Disaster Relief and Emergency Assistance Act	Activated after a presidential disaster declaration; provides funds on a sliding scale formula based on a percentage of the total federal assistance for a disaster for long-term mitigation measures to reduce vulnerability to natural hazards

Mitigation Grant Program	Authorization	Purpose
Flood Mitigation Assistance (FMA)	National Flood Insurance Reform Act	Reduce or eliminate claims against the NFIP
Pre-Disaster Mitigation (PDM)	Disaster Mitigation Act	National competitive program focused on mitigation project and planning activities that address multiple natural hazards
Repetitive Flood Claims (RFC)	Bunning-Bereuter-Blumenauer Flood Insurance Reform Act	Reduce flood claims against the NFIP through flood mitigation; properties must be currently NFIP insured and have had at least one NFIP claim
Severe Repetitive Loss (SRL)	Bunning-Bereuter-Blumenauer Flood Insurance Reform Act	Reduce or eliminate the long-term risk of flood damage to SRL residential structures currently insured under the NFIP

The HMGP and PDM programs offer funding for mitigation planning and project activities that address multiple natural hazard events. The FMA, RFC, and SRL programs focus funding efforts on reducing claims against the NFIP. Funding under the HMA programs is subject to availability of annual appropriations, and HMGP funding is also subject to the amount of FEMA disaster recovery assistance provided under a presidential major disaster declaration.

FEMA's HMA grants are awarded to eligible states, tribes, and territories (applicant) that, in turn, provide sub-grants to local governments and communities (sub-applicant). The applicant selects and prioritizes sub-applications developed and submitted to them by sub-applicants and submits them to FEMA for funding consideration. Prospective sub-applicants should consult the office designated as their applicant for further information regarding specific program and application requirements. Contact information for the FEMA Regional Offices and State Hazard Mitigation Officers (SHMO) is available on the FEMA website (www.fema.gov).

4.3.2 Additional Mitigation Programs and Assistance

Several additional agencies including USACE, Natural Resource Conservation Service (NRCS), U.S. Geological Survey (USGS), and others have specialists on staff and can offer further information on flood hazard mitigation. The State NFIP Coordinator and SHMO are state-level sources of information and assistance, which vary among different states.

The Silver Jackets program, active in several states, is a partnership of USACE, FEMA, and state agencies. The Silver Jackets program provides a state-based strategy for an interagency approach to planning and implementing measures for risk reduction.

5 Acronyms and Definitions

5.1 Acronyms

A

ADCIRC	The Advanced Circulation Model
AAL	Average Annualized Loss
ALR	Annualized Loss Ratio
<i>AoMI</i>	<i>Areas of Mitigation Interest</i>

B

BCA	Benefit-Cost Analysis
BFE	Base Flood Elevation
BMP	Best Management Practices

C

CFR	Code of Federal Regulations
COG	Continuity of Government Plan
COOP	Continuity of Operations Plan
CRS	Community Rating System
CSLF	Changes Since Last FIRM

D

DHS	Department of Homeland Security
DMA 2000	Disaster Mitigation Act of 2000

E

EOP	Emergency Operations Plan
-----	---------------------------

F

FEMA	Federal Emergency Management Agency
FIRM	Flood Insurance Rate Map
FIS	Flood Insurance Study
FMA	Flood Mitigation Assistance
FRD	Flood Risk Database
FRM	Flood Risk Map
FRR	Flood Risk Report
FY	Fiscal Year

G

GIS	Geographic Information System
-----	-------------------------------

H

HMA	Hazard Mitigation Assistance
HMGP	Hazard Mitigation Grant Program

I

IA Individual Assistance

N

NFIA National Flood Insurance Act

NFIP National Flood Insurance Program

NRCS Natural Resource Conservation Service

P

PA Public Assistance

PDM Pre-Disaster Mitigation

R

RFC Repetitive Flood Claims

Risk MAP Mapping, Assessment, and Planning

S

SFHA Special Flood Hazard Area

SHMO State Hazard Mitigation Officer

SRL Severe Repetitive Loss

U

USACE U.S. Army Corps of Engineers

USGS U.S. Geological Survey

W

WHAFIS Wave Height Analysis for Flood Insurance Studies

5.2 Definitions

0.2-percent-annual-chance flood – The flood elevation that has a 0.2-percent chance of being equaled or exceeded each year. Sometimes referred to as the 500-year flood.

1-percent-annual-chance flood – The flood elevation that has a 1-percent chance of being equaled or exceeded each year. Sometimes referred to as the 100-year flood.

Annualized Loss Ratio (ALR) – Expresses the annualized loss as a fraction of the value of the local inventory (total value/annualized loss).

Average Annualized Loss (AAL) – The estimated long-term weighted average value of losses to property in any single year in a specified geographic area.

Base Flood Elevation (BFE) – Elevation of the 1-percent-annual-chance flood. This elevation is the basis of the insurance and floodplain management requirements of the NFIP.

Berm – A small levee, typically built from earth.

Cfs – Cubic feet per second, the unit by which discharges are measured (a cubic foot of water is about 7.5 gallons).

Consequence (of flood) – The estimated damages associated with a given flood occurrence.

Crest – The peak stage or elevation reached or expected to be reached by the floodwaters of a specific flood at a given location.

Dam – An artificial barrier that has the ability to impound water, wastewater, or any liquid-borne material, for the purpose of storage or control of water.

Design flood event – The greater of the following two flood events: (1) the base flood, affecting those areas identified as SFHAs on a community's FIRM; or (2) the flood corresponding to the area designated as a flood hazard area on a community's flood hazard map or otherwise legally designated.

Erosion – Process by which floodwaters lower the ground surface in an area by removing upper layers of soil.

Essential facilities – Facilities that, if damaged, would present an immediate threat to life, public health, and safety. As categorized in Hazus, essential facilities include hospitals, emergency operations centers, police stations, fire stations, and schools.

Flood – A general and temporary condition of partial or complete inundation of normally dry land areas from (1) the overflow of inland or tidal waters or (2) the unusual and rapid accumulation or runoff of surface waters from any source.

Flood Insurance Rate Map (FIRM) – An official map of a community, on which FEMA has delineated both the SFHAs and the risk premium zones applicable to the community. See also Digital Flood Insurance Rate Map.

Flood Insurance Study (FIS) Report – Contains an examination, evaluation, and determination of the flood hazards of a community, and if appropriate, the corresponding water-surface elevations.

Flood risk – Probability multiplied by consequence; the degree of probability that a loss or injury may occur as a result of flooding. This is sometimes referred to as flood vulnerability.

Flood vulnerability – Probability multiplied by consequence; the degree of probability that a loss or injury may occur as a result of flooding. This is sometimes referred to as flood risk.

Flood-borne debris impact – Floodwater moving at a moderate or high velocity can carry flood-borne debris that can impact buildings and damage walls and foundations.

Floodwall – A long, narrow concrete or masonry wall built to protect land from flooding.

Floodway (regulatory) – The channel of a river or other watercourse and that portion of the adjacent floodplain that must remain unobstructed to permit passage of the base flood without cumulatively increasing the water surface elevation more than a designated height (usually 1 foot).

Floodway fringe – The portion of the SFHA that is outside of the floodway.

Freeboard – A factor of safety usually expressed in feet above a flood level for purposes of flood plain management. “Freeboard” tends to compensate for the many unknown factors that could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions, such as wave action, bridge openings, and the hydrological effect of urbanization of the watershed (44CFR§59.1).

Hazus – A GIS-based risk assessment methodology and software application created by FEMA and the National Institute of Building Sciences for analyzing potential losses from floods, hurricane winds and storm surge, and earthquakes.

High velocity flow – Typically comprised of floodwaters moving faster than 5 feet per second.

Levee – A human-made structure, usually an earthen embankment, designed and constructed in accordance with sound engineering practices to contain, control, or divert the flow of water so as to provide protection from temporary flooding. (44CFR§59.1)

Loss ratio – Expresses loss as a fraction of the value of the local inventory (total value/loss).

Mudflow – Mudslide (i.e., mudflow) describes a condition where there is a river, flow or inundation of liquid mud down a hillside usually as a result of a dual condition of loss of brush cover, and the subsequent accumulation of water on the ground preceded by a period of unusually heavy or sustained rain. A mudslide (i.e., mudflow) may occur as a distinct phenomenon while a landslide is in progress, and will be recognized as such by the Administrator only if the mudflow, and not the landslide, is the proximate cause of damage that occurs. (44CFR§59.1)

Probability (of flood) – The likelihood that a flood will occur in a given area.

Risk MAP – Risk Mapping, Assessment, and Planning, a FEMA strategy to work collaboratively with state, local, and tribal entities to deliver quality flood data that increases public awareness and leads to action that reduces risk to life and property.

Riverine – Of or produced by a river. Riverine floodplains have readily identifiable channels.

Special Flood Hazard Area (SFHA) – Portion of the floodplain subject to inundation by the 1-percent-annual or base flood.

Stafford Act – Robert T. Stafford Disaster Relief and Emergency Assistance Act, PL 100-707, signed into law November 23, 1988; amended the Disaster Relief Act of 1974, PL 93-288. This Act constitutes the statutory authority for most federal disaster response activities especially as they pertain to FEMA and FEMA programs.

Stillwater –Projected elevation that flood waters would assume, referenced to National Geodetic Vertical Datum of 1929, North American Vertical Datum of 1988, or other datum, in the absence of waves resulting from wind or seismic effects.

Stream Flow Constrictions – A point where a human-made structure constricts the flow of a river or stream.

6 Additional Resources

ASCE 7 – National design standard issued by the American Society of Civil Engineers (ASCE), *Minimum Design Loads for Buildings and Other Structures*, which gives current requirements for dead, live, soil, flood, wind, snow, rain, ice, and earthquake loads, and their combinations, suitable for inclusion in building codes and other documents.

ASCE 24-05 – National design standard issued by the ASCE, *Flood Resistant Design and Construction*, which outlines the requirements for flood resistant design and construction of structures in flood hazard areas.

National Flood Insurance Program (NFIP), Federal Emergency Management Agency (FEMA), www.floodsmart.gov

FEMA, www.fema.gov

ASCE, 2010. *So, You Live Behind a Levee!* Reston, VA.

FEMA Publications – available at www.fema.gov

FEMA, 1985. *Manufactured Home Installation in Flood Hazard Areas*, FEMA 85. Washington, DC, September 1985.

FEMA and the American Red Cross, 1992. *Repairing Your Flooded Home*, FEMA 234/ARC 4476. Washington, DC, August 1992.

FEMA, 1996. *Addressing Your Community's Flood Problems*, FEMA 309. Washington, DC, June 1996.

FEMA, 1998. *Homeowner's Guide to Retrofitting*, FEMA 312. Washington, DC, June 1998.

FEMA, 1999. *Protecting Building Utilities from Flood Damage*, FEMA 348. Washington, DC, November 1999.

FEMA, 1999. *Riverine Erosion Hazard Areas Mapping Feasibility Study*. Washington, DC, September 1999.

FEMA, 2003. *Interim Guidance for State and Local Officials - Increased Cost of Compliance Coverage*, FEMA 301. Washington, DC, September 2003.

FEMA, 2000. *Above the Flood: Elevating Your Floodprone House*, FEMA 347. Washington, DC, May 2000.

FEMA, 2001. *Understanding Your Risks: Identifying Hazards and Estimating Losses*, FEMA 386-2. Washington, DC, August 2001.

FEMA, 2002a. *Getting Started: Building Support for Mitigation Planning*, FEMA 386-1. Washington, DC, September 2002.

FEMA, 2002b. *Integrating Manmade Hazards into Mitigation Planning*, FEMA 386-7. Washington, DC, September 2002.

FEMA, 2003a. *Developing the Mitigation Plan: Identifying Mitigation Actions and Implementing Strategies*, FEMA 386-3. Washington, DC, April 2003.

FEMA, 2003b. *Bringing the Plan to Life: Implementing the Hazard Mitigation Plan*, FEMA 386-4. Washington, DC, August 2003.

FEMA, 2004a. *Design Guide for Improving School Safety in Earthquakes, Floods, and High Winds*, FEMA 424. Washington, DC, January 2004.

FEMA, 2004b. *Federal Guidelines for Dam Safety: Emergency Action Planning for Dam Owners*, FEMA 64. Washington, DC, April 2004.

FEMA, 2005. *Integrating Historic Property and Cultural Resource Considerations into Hazard Mitigation Planning*, FEMA 386-6. Washington, DC, May 2005.

FEMA, 2006a. *Multi-Jurisdictional Mitigation Planning*, FEMA 386-8. Washington, DC, August 2006.

FEMA, 2006b. *Using the Hazard Mitigation Plan to Prepare Successful Mitigation Projects*, FEMA 386-9. Washington, DC, August 2008.

FEMA, 2006c. *“Designing for Flood Levels Above the BFE,” Hurricane Katrina Recovery Advisory 8, Hurricane Katrina in the Gulf Coast: Building Performance Observations, Recommendations, and Technical Guidance*, FEMA 549, Appendix E. Washington, DC, July 2006.

FEMA, 2007a. *Property Acquisition Handbook for Local Communities*, FEMA 317. Washington, DC, September 2007.

FEMA, 2007b. *Public Assistance Guide*, FEMA 322. Washington, DC, June 2007.

FEMA, 2007c. *Using Benefit-Cost Review in Mitigation Planning*, FEMA 386-5. Washington, DC, May 2007.

FEMA, 2007d. *Design Guide for Improving Critical Facility Safety from Flooding and High Winds: Providing Protection to People and Buildings*, FEMA 543. Washington, DC, January 2007.

FEMA, 2007e. *Selecting Appropriate Mitigation Measures for Floodprone Structures*, FEMA 551. Washington, DC, March 2007.

FEMA, 2007f. *Design Guide for Improving Hospital Safety in Earthquakes, Floods, and High Winds: Providing Protection to People and Buildings*, FEMA 577. Washington, DC, June 2007.

FEMA, 2008. *Reducing Flood Losses Through the International Codes: Meeting the Requirements of the National Flood Insurance Program*, FEMA 9-0372, Third Edition. Washington, DC, December 2007.

7 Data Used to Develop Flood Risk Products

GIS base map information was acquired primarily from the following sources:

- FEMA
- Texas Natural Resources Information System (TNRIS)
- Texas Water Development Board
- South East Texas Regional Planning Commission
- USDA

Corporate limits, roads, and hydrographic features were obtained from FEMA's most recent countywide FIRM update or from the TNRIS StratMap product.

Engineering study information was leveraged from the USACE and FEMA.

Hazard Mitigation Plan information was provided by the South East Texas Regional Planning Commission.

Flood Insurance Claim, Policy, and additional Mitigation Plan information were acquired from FEMA.

Photos shown on the Flood Risk Map were taken from publically available sources on the Internet.

Census Information

All Census information was collected from FEMA's Hazus version 2.1 software product. For more detailed information on the Census data and currency, see the metadata file for the Flood Risk Database.

HUC8 Boundary

HUC boundaries were provided by the USDA.

Hillshade

A grayscale image showing elevation topographic data is shown on the background of the Flood Risk Map. These data were collected from the Texas Water Development Board. This data layer is called a "Hillshade" in the Flood Risk Database.

Changes Since Last FIRM (CSLF)

CSLF are provided both for the project area, only as summarized in this Flood Risk Report, and as a complete countywide product as developed for the most recent map revision of the Flood Insurance Rate Map (FIRM). Please refer to <http://www.txchart.com> for any floodway changes.

General Building Stock

General Building Stock represents the total economic inventory for a community (i.e. and estimate of the replacement dollar cost for all buildings and their content). Updated General Building data provided by the Texas Water Development Board (TWDB) was used during Risk Assessment in Hazus; those results are reflected in this report.